

Product Name:	ABT-AFPP-23
Description:	<p>Premier Stainless Steel Auto Defrost Laboratory Freezer 23 Cu. Ft. Capacity One swing stainless steel door Multi-Point temperature mapping via NIST traceable data acquisition, 15 probes in air and 3 probes in sample solution for 360 minutes with temperature readings every 60 seconds Digital Temperature Display & Alarm Module: Microprocessor Temperature Controller Adjustable operating temperature range: -15°-25°C Digital Temperature Display and Alarm Module Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Three shelves (adjustable in ½" increments) Keyed door locks Magnetic door gasket for positive seal Recessed door handle Swivel casters (adds 5" to height; included in dimensions) Interior light Probe access port (3/8") 300 Series stainless steel interior/exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R290), foam insulation and packaging Two year parts and labor warranty, plus an additional three year compressor parts warranty Exterior dimensions: 27"W x 30 3/4"D x 83 1/4"H with casters. 78 1/4"H without casters Auto defrost 115V, 60 Hz, 3.7 Amps, 1/2 HP, BTU/HR 4932 UL/C-UL listed Shipping weight: 310 lbs. DISCLAIMER: Auto defrost freezers incorporate an electric heater installed on the evaporator that assist in the removal of the frost and ice. Although the heater helps speed up the frost and ice removal, it can raise the temperatures within the freezer.</p>