Product Name:	ABT-FFP-17
Description:	17 Cu. Ft. capacity One solid swing door, right hinged, not reversible Microprocessor Temperature Controller Adjustable operating temperature range: -15°-25°C Digital Temperature Display and Alarm Module Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Three fixed shelves Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Leveling legs One probe access port (3/8") White textured cabinet and door High density urethane foam cabinet and door insulation CFC-free refrigerant (R134a), foam insulation and packaging Two year parts and labor warranty Exterior dimensions: 34"W x 32 1/4" D x 71 3/8"H Manual defrost 115V, 60 Hz, 5 Amps, 1/3 HP UL/C-UL listed Units meet NFPA guidelines 45 and 70
	White textured cabinet and door High density urethane foam cabinet and door insulation CFC-free refrigerant (R134a), foam insulation and packaging Two year parts and labor warranty Exterior dimensions: 34"W x 32 1/4" D x 71 3/8"H Manual defrost 115V, 60 Hz, 5 Amps, 1/3 HP UL/C-UL listed