

Product Name:	ABT-HC-12S
Description:	<p>Premier Solid Door Laboratory Refrigerator  12 Cu. Ft. capacity  One swing solid door, self-closing, right hinged, not reversible  Microprocessor Temperature Controller  Adjustable operating temperature range: 1°-10°C  Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms  Sample simulated digital temperature display; .1° Resolution  Adjustable temperature display in Celsius or Fahrenheit  Audible and visual high/low temperature alarms  2 probes; 1 in air and 1 in sample bottle  Sensor error alarm  Power failure alarm  Resettable 1-point Min/Max History  Remote alarm contacts  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Three adjustable shelves (adjustable in ½" increments)  Forced draft air circulation  Keyed door lock  LED interior lights are safety shielded and switch controlled  Swivel casters (3 ½")  probe access port (3/8")  White powder-coated steel exterior and interior  Hydrocarbon, natural refrigerant (R290)  Two year parts and labor warranty, plus an additional three compressor parts warranty  Exterior dimensions: 25" W x 29 ¾" D x 65 ¾" H with casters; 62 ¼" H without casters  Cycle defrost  115V, 60 Hz, 6 Amps, 3/8 HP  ETL listed  Shipping weight: 227 lbs.</p>