

Product Name:	ABT-HC-35C
Description:	<p>Premier Glass Door Chromatography Refrigerator 35 Cu. Ft. capacity Two swing glass doors, self-closing (energy efficient, double pane vacuum insulated) Microprocessor Temperature Controller Adjustable operating temperature range: 1°-10°C Standard Digital Temperature Display and Alarm Module Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Eight adjustable shelves (adjustable in ½" increments) Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Recessed door handle LED interior lights are safety shielded and switch controlled Swivel casters (adds 4" to height) One GFCI protected duplex electrical outlet Two 2" access ports with spring loaded self-closing, gasketed metal covers Probe access port (3/8") White laminated vinyl exterior White aluminum liner and stainless steel floor interior HFC-free refrigerant (R290), foam insulation and packaging Three year parts and labor warranty, plus an additional two year compressor parts warranty Exterior dimensions: 41" W x 31 3/4" D x 82 5/8" H with casters; 78 5/8" H without casters. *Width w/access ports closed; 49" width w/access ports open Cycle defrost 115V, 60 Hz, 6.2 Amps, 1/3 HP, BTU/HR 5265 UL/C-UL listed Shipping weight: 425 lbs. Note: This unit requires two (2) outlets</p>