

Product Name:	ABT-HC-72S-TS
Description:	<p>TempLog Premier Solid Door Laboratory Refrigerator</p> <p>72 Cu. Ft. capacity</p> <p>Three swing solid doors, self-closing, right hinged, not reversible</p> <p>Microprocessor temperature controller</p> <p>Adjustable operating temperature range: 1°C - 10°C</p> <p>TempData-2000 Touch Screen Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms</p> <p>Password-protected control panel</p> <p>Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit</p> <p>Active temperature scale bar display</p> <p>Resettable 1-point min/max history</p> <p>Digital 24-hour temperature chart</p> <p>Temperature data logging</p> <p>USB port for data transfer and software updates</p> <p>Real-time operational display clock</p> <p>4-20mA output</p> <p>Electronic troubleshooting guide</p> <p>Electronic QR Code to access Owner's Manual & technical support contact information</p> <p>Adjustable alarm volume</p> <p>Audible and visual high/low temperature alarms</p> <p>2 probes; 1 in air and 1 in sample bottle</p> <p>Sensor error alarm</p> <p>Power failure alarm</p> <p>Door ajar alarm</p> <p>Low battery alarm</p> <p>Operation indicator</p> <p>Alarm validation (audible, visual, and remote alarm)</p> <p>Alarm mute with ring back</p> <p>Remote alarm contacts</p> <p>Twelve adjustable shelves (adjustable in ½" increments)</p> <p>Forced draft air circulation</p> <p>Keyed door locks</p> <p>Magnetic door gasket for positive seal</p> <p>Heavy duty door handles</p> <p>LED interior lights are safety shielded and switch controlled</p> <p>Swivel casters (3 ½")</p> <p>Probe access port (3/8")</p> <p>White powder-coated steel exterior and interior</p> <p>Hydrocarbon, natural refrigerant (R290)</p> <p>Three year parts and labor warranty, plus an additional two year compressor parts warranty</p> <p>Exterior dimensions: 81" W x 34" D x 81 ¾" H with casters; 78 ¼" H without casters</p> <p>Cycle defrost</p> <p>115V, 60 Hz, 10 Amps, 3/4 HP</p> <p>ETL listed</p> <p>Shipping weight: 600 lbs.</p>