

Product Name:	ABT-HC-UCFS-0120A
Description:	<p>Premier Countertop Auto Defrost Laboratory Freezer  Freestanding  1.3 Cu. Ft. Capacity  One solid swing door, right hinged*  Microprocessor temperature controller  Digital temperature display  Audible and visual high and low temperature alarms  Remote alarm contacts  2 probes; 1 in air and 1 in sample bottle  Adjustable operating temperature range: -15°C – -25°C  Auto defrost cycle every 6 hours, max air temp in empty freezer: +4.34°C; max air temp in loaded freezer: -2.89°C. Max sample temp in empty freezer: -4.76°C; max sample temp in loaded freezer: -9.58°C.  2 adjustable shelves with guard rail to prevent product from being pushed against back wall  Bottom footed shelf to allow air circulation  Keyed door lock  Magnetic door gasket for positive seal  Leveling legs  Probe access port (3/8")  Powder coat exterior  High density urethane foam cabinet and door insulation  HFC-free refrigerant (R600a), foam insulation and packaging  Two year parts and labor warranty  Pyxis®, Omnicell® and AcuDose RX® compatible  Exterior dimensions: 23 ¾ "W x 24" D x 20 3/8"H  <i>Note: This unit must have 4" clearance on sides and back for adequate ventilation</i>  Auto defrost  115V, 60 Hz, 1 Amp, 1/8 HP  Energy Consumption 1.4 kWh/day  ADA compliant  UL/C-UL listed  ENERGY STAR CERTIFIED  Shipping weight: 106 lbs.  *This product is available left hinged, product number ABT-HC-UCFS-0120A-LH  DISCLAIMER: Auto defrost freezers incorporate an electric heater installed on the evaporator that assist in the removal of the frost and ice. Although the heater helps speed up the frost and ice removal, it can raise the temperatures within the freezer.</p>