	og Premier Manual Defrost Laboratory Freezer
	Ft. capacity
	id swing door, right hinged, not reversible
	ner "fast-freeze compartments" with doors for temperature
	nance and recovery
	ocessor Temperature Controller
	ble Operating Temperature Range: 15°- 25°C
	Screen Digital Temperature Display and Alarm Module
	ord-protected Control Panel
	simulated digital temperature display; .1° Resolution, adjustable
	ature display in Celsius or Fahrenheit
	emperature Scale Bar Display
	ble 1-point Min/Max History
	24-hour Temperature Chart
	rature Data Logging
	ort for Data Transfer and Software Updates
	ne Operational Display Clock
	Output
	nic Troubleshooting Guide
Informa	nic QR Code to Access Owner's Manual & Technical Support Contact
	ble Alarm Volume
	and Visual High/Low Temperature Alarms
	Error Alarm
	Failure Alarm
	ar Alarm
	ttery Alarm
	on Indicator
	/alidation (audible, visual, and remote alarm)
	Nute with Ring Back
	Alarm Contacts
	xed shelves
	door lock
	ic door gasket for positive seal
	duty door handle
	platform (adds 4" to height)
	obe access port (3/8")
	extured cabinet and door
	nsity urethane foam cabinet and door insulation
	ee refrigerant (R134a), foam insulation and packaging
	ear parts and labor warranty, plus additional two year compressor parts
warrant	· · · · · · · · · · · · · · · · · · ·
Exterior	dimensions: 34"W x 30 ¾"D x 71 ½"H with caster platform; 67 ½"H
without	caster platform
Manual	defrost
115V, 6	0 Hz, 5 Amps, 1/3 HP
UL/C-U	
Shippin	g weight: 265 lbs.