

| | |
|---------------|---|
| Product Name: | ABT-MFP-20-TS |
| Description: | <p>TempLog Premier Manual Defrost Laboratory Freezer 20 Cu. Ft. capacity One solid swing door, right hinged, not reversible Five inner "fast-freeze compartments" with doors for temperature maintenance and recovery Microprocessor Temperature Controller Adjustable Operating Temperature Range: -15°- -25°C Touch Screen Digital Temperature Display and Alarm Module Password-protected Control Panel Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit Active Temperature Scale Bar Display Resettable 1-point Min/Max History Digital 24-hour Temperature Chart Temperature Data Logging USB Port for Data Transfer and Software Updates Real-time Operational Display Clock 4-20mA Output Electronic Troubleshooting Guide Electronic QR Code to Access Owner's Manual & Technical Support Contact Information Adjustable Alarm Volume Audible and Visual High/Low Temperature Alarms Sensor Error Alarm Power Failure Alarm Door Ajar Alarm Low Battery Alarm Operation Indicator Alarm Validation (audible, visual, and remote alarm) Alarm Mute with Ring Back Remote Alarm Contacts Four fixed shelves Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Caster platform (adds 4" to height) One probe access port (3/8") White textured cabinet and door High density urethane foam cabinet and door insulation CFC-free refrigerant (R134a), foam insulation and packaging Three year parts and labor warranty, plus additional two year compressor parts warranty Exterior dimensions: 34"W x 32 ¾"D x 77 ¼"H with caster platform; 73 ¼"H without caster platform Manual defrost 115V, 60 Hz, 5 Amps, 1/3 HP UL/C-UL listed Shipping weight: 314 lbs.</p> |