

|               |  |
|---------------|--|
| Product Name: | ABT-MFP-2030-TS  |
| Description:  | <p>TempLog Premier Manual Defrost Laboratory Freezer, -30C<br/> 20 Cu. Ft. capacity<br/> One solid swing door, right hinged, not reversible<br/> Five inner "fast-freeze compartments" with doors for temperature maintenance and recovery<br/> Microprocessor temperature controller:<br/> Adjustable operating temperature range: -27°C – -33°C<br/> Touch Screen Digital Temperature Display and Alarm Module<br/> Password-protected control panel<br/> Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit<br/> Active temperature scale bar display<br/> Resettable 1-point min/max history<br/> Digital 24-hour temperature chart<br/> Temperature data logging<br/> USB port for data transfer and software updates<br/> Real-time operational display clock<br/> 4-20mA output<br/> Electronic troubleshooting guide<br/> Electronic QR Code to access Owner's Manual &amp; technical support contact Information<br/> Adjustable alarm volume<br/> Audible and visual high/low temperature alarms<br/> Sensor error alarm<br/> Power failure alarm<br/> Door ajar alarm<br/> Low battery alarm<br/> Operation indicator<br/> Alarm validation (audible, visual, and remote alarm)<br/> Alarm mute with ring back<br/> Remote alarm contacts<br/> Four fixed shelves<br/> Keyed door lock<br/> Magnetic door gasket for positive seal<br/> Heavy duty door handle<br/> Caster platform (adds 4" to height)<br/> One probe access port (3/8")<br/> White textured cabinet and door<br/> High density urethane foam cabinet and door insulation<br/> CFC-free refrigerant (R134a), foam insulation and packaging<br/> Three year parts and labor warranty, plus additional two year compressor parts warranty<br/> Exterior dimensions: 34"W x 32 ¾"D x 77 ¼"H with caster platform; 73 ¼"H without caster platform<br/> Manual defrost<br/> 115V, 60 Hz, 5 Amps, 1/3 HP<br/> UL/C-UL listed<br/> Shipping weight: 314 lbs.</p> |