

Product Name:	ABT-RFC-16A
Description:	<p>Premier Refrigerator & Freezer Combination 16 cu. ft. capacity (13 cu. ft. refrigerator/3 cu. ft. freezer) Two exterior solid swing, double insulated doors, right hinged, not reversible Individual microprocessor temperature controllers for both the refrigerator and freezer Independent temperature displays Adjustable operating temperature range: Refrigerator: 1°C – 10°C; Freezer: -15°C -- -25°C Sample temperature in freezer does not rise above -20°C during defrost cycle Both chambers feature forced draft circulation / fan driven air circulation Uniformity of samples throughout the freezer ($\pm 2^{\circ}\text{C}$ throughout chamber) Uniformity of samples throughout the refrigerator ($\pm 1^{\circ}\text{C}$ throughout chamber) 36 hour battery back-up on alarms, high/low temperature & loss of power Two isolated audible & visual high/low alarm systems remote alarm contacts Two independent mechanical Refrigeration systems; 1 compressor -Refrigerator, 1 compressor – Freezer Remote alarm contacts, refrigerator & freezer 3 adjustable, vented stainless steel shelves refrigerator/ 1 fixed shelf freezer Leveling legs Keyed door locks, refrigerator & freezer Magnetic door gasket for positive seal Heavy duty door handles Probe access port (3/8"), 2 ea. (1 for refrigerator/1 for freezer) White powder coated exterior CFC-free refrigerant (R134a), foam insulation and packaging Two year parts and labor warranty, plus an additional three year compressor parts warranty Exterior dimensions: 29 1/2"W x 34 3/4"D x 78"H Auto defrost freezer / cycle defrost refrigerator 115 V, 60Hz, 7.5 Amps, 1/8 HP UL/C-UL listed Shipping weight: 323 lbs. DISCLAIMER: Auto defrost freezers incorporate an electric heater installed on the evaporator that assist in the removal of the frost and ice. Although the heater helps speed up the frost and ice removal, it can raise the temperatures within the freezer.</p>

--	--