

Product Name:	CRT-ABT-HC-UCFS-0104G-LH
Description:	<p>Undercounter Controlled Room Temperature Cabinet, Freestanding-LEFT HINGED</p> <p>1 Cu. Ft. Capacity</p> <p>One glass swing door, left hinged</p> <p>Microprocessor temperature controller</p> <p>Digital temperature display</p> <p>Audible and visual high and low temperature alarms</p> <p>Remote alarm contacts</p> <p>2 probes; 1 in air and 1 in sample bottle</p> <p>Adjustable operating temperature range: 68°F–77°F (20°C – 25°C)</p> <p>Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm</p> <p>2 adjustable shelves</p> <p>Back wall evaporator cover</p> <p>Vaccine storage power cord warning label</p> <p>Forced draft circulation</p> <p>Keyed door lock</p> <p>Integrated door handle</p> <p>Magnetic door gasket for positive seal</p> <p>Leveling legs</p> <p>LED interior light</p> <p>Probe access port (3/8")</p> <p>Powder coat exterior</p> <p>High density urethane foam cabinet and door insulation</p> <p>HFC-free refrigerant (R600a), foam insulation and packaging</p> <p>Two year parts and labor warranty</p> <p>Pyxis®, Omnicell® and AcuDose RX® compatible</p> <p>Exterior dimensions: 17 ¼"W x 19 ¼"D x 21 ¼"H</p> <p><i>Note: This unit must have 4" clearance on sides and back for adequate ventilation</i></p> <p>Cycle defrost</p> <p>115V, 60 Hz, .90 Amps, 1/8 HP</p> <p>UL/C-UL listed</p> <p>Shipping weight: 91 lbs.</p>