

Coming soon

DEP-600/DEP-300HC

Electrophoresis power supplies

We offer user-friendly and powerful electrophoresis power supplies for gel electrophoresis, blotting, and other demanding applications. The DEP series features an LCD touchscreen interface for easy programming and supports simultaneous use of four output sockets with three operating modes: constant voltage, constant current, and constant power.



NEW

Features

- LCD Touchscreen: Simple programming and progress tracking.
- High Precision: Adjustable voltage, current, and power with automatic mode switching.
- Real-time Data Recording: USB support for data analysis.
- Easy Programming: Multi-step programs with tabular entry.
- Stable Performance: Multi-CPU control ensures reliability.
- Power Failure Recovery: ON/OFF setting based on experimental needs.
- Low Current Maintenance: ON/OFF setting as needed.
- Safety Protection and Alarm: Short-circuit protection, no-load protection, and a buzzer that can be set according to experimental needs.
- Space-saving Design: Anti-slip grooves enable stacking multiple power supplies, saving lab space.
- Multiple Outputs: Four sockets for simultaneous use of four electrophoresis units.

Coming soon



Pop-up feet



Anti-slip groove design



Real-time data recording



Low-noise, High-efficiency cooling fan

Applications

The DEP-600 power supply covers the broadest range of applications in the market, meeting the power needs of small vertical electrophoresis, high-throughput electrophoresis, and blotting. It supports applications such as SDS-PAGE, Native-PAGE, common protein, and DNA/RNA electrophoresis.

Specifications	DEP-600	DEP-300HC
Display	LCD touchscreen	LCD touchscreen
Output Types	Constant Voltage, Constant Current, Constant Power (continuously adjustable)	Constant Voltage, Constant Current, Constant Power (continuously adjustable)
Voltage Range	0~600V	0~300V
Current Range	0~600mA	0~3000mA
Power Range	0~360W	0~400W
Resolution	Voltage (1V), Current (1mA), Power (1W)	Voltage (1V), Current (1mA), Power (1W)
Time Setting Range	1min ~ 99h59min	1min ~ 99h59min
Interface	USB	USB
Output Sockets	4 sets	4 sets
Voltage	100-120V/200-240V,50/60Hz	100-240V,50/60Hz
Operating Temperature and Humidity	0°C~40°C, ≤95%	0°C~40°C, ≤95%
Dimensions (L×W×H)	310×260×115mm	310×260×115mm
Weight	1.96kg	2.05kg