

## *SO-LOW EXPLOSION PROOF REFRIGERATOR MODEL DHH4-20SDRX MANUAL DEFROST*

*Meets NFPA and OSHA guidelines for Hazardous Locations, Class I, Division II, Group C & D.*

### **20 Cubic Ft. Upright +4°C / Solid Door**

#### **Specifications:**

|                      |                           |
|----------------------|---------------------------|
| * Capacity           | 20 cubic ft. / 566 liters |
| * Temperature        | 1°C to 10°C               |
| * Dimensions         |                           |
| * Exterior w x d x h | 34.75" x 29" x 74.50"     |
| * Interior w x d x h | 24.75" x 20.75" x 65.25"  |

#### **Features:**

|                      |   |
|----------------------|---|
| *Thermostat          | *Microprocessor temperature controller                |
|                      | *Remote alarm contacts                                |
|                      | *Audible and visual high/low temperature alarms       |
|                      | *Alarm validation (audible, visual, and remote alarm) |
| *Compressor          | 1/4 Hp Compressor                                     |
| *Doors               | Single solid – key lock                               |
| *Legs                | Four leveling   |
| *Shelves             | 5 shelves   |
| *Insulation:         | High density urethane foam                            |
| *Refrigerant:        | R-600A  |
| *Air Circulation     | Fan   |
| *Defrost             | Cycle   |
| *Voltage             | 115-60-1  |
| *Running Amps        | 3   |
| *Supply Plug         | Not supplied (hardwire)                               |
| *Shipping weight     | 260 lbs.  |
| *Approvals           | ETL Listed  |
| *Warranty-(Domestic) | Two year parts and labor.                             |



Specifications subject to change without notice