

# Pharmacy Refrigerator

— **HYC-610**



## Ergonomic Design



### LED Temperature Display

- Display precision 0.1°C.



### Multiple Alarm Functions

- Alarms including high and low temperature, remote alarm, sensor error, power failure, low battery, door ajar.



### Adjustable Shelves

- The shelves are adjustable to any height to fulfill different user requirements.



### Large Storage Space



### Lockable Design



### Self Closing Door with 90° Stay Open Feature

**Qingdao Haier Biomedical Co.,Ltd.**

No.280 Feng Yuan Road, High-tech Zone,  
Qingdao, 266109, P.R. China  
Tel: +86-0532-88935593  
Website: [www.haiermedical.com](http://www.haiermedical.com)



Haier Biomedical  
International



Haier Biomedical  
International



@haiermedicalint



Haier Biomedical  
International



Haier Biomedical  
International

# Intelligent Reagent Refrigerator

## — HYC-610

### Product Advantages



#### Energy Efficient Hydrocarbon (HC) Refrigeration System

Imported efficient inverter compressor with optimized cooling system, more energy efficient.



#### Greener by Design

Hydrocarbon compressor and refrigerant, the refrigerant does not contain any fluorine or chlorine, greener and environmentally friendly.



#### Energy conserving, maintains temperature uniformity to protect valuable samples.



#### Superior cabinet temperature uniformity, automatic defrosting

The distribution point for performance tests in the cabinet increased from 2 to 9 points.



HYC-610

### Specifications

Model	HYC-610			
Technical Data	Cabinet Type	Upright, single door	Upright, single door	
	Climate Class	N	N	
	Cooling Type	Forced air cooling	Forced air cooling	
	Defrost Mode	Auto	Auto	
	Refrigerant	HC	HC	
	Noise (dB (A))	43	45	
Performance	Temp Range (°C)	2-8	2-8	
Control	Controller	Microprocessor	Microprocessor	
	Display	LED	LED	
Electrical Data	Power Supply (V/Hz)	220-240/50&60	115/60	
	Power (W)	550	500	
	Electrical Current (A)	3	6.2	
Alarms	High/Low Temp	Y	Y	
	Remote System	Y	Y	
	Power Failure	Y	Y	
	Sensor Error	Y	Y	
	Low Battery	Y	Y	
	Door Ajar	Y	Y	
Accessories	Caster	Y	Y	
	Foot	Y	Y	
	Porthole	Y	Y	
	Shelves/Basket	6/-	6/-	
	Temperature Recorder	Optional	Optional	
	USB Interface	Optional	Optional	
Dimensions	Capacity (L/Cu.Ft)	610/21.6	610/21.6	
	Net/Gross Weight (approx)	kg	204/227	204/227
		lbs	449.7/500.4	449.7/500.4
	Interior Dimensions (W*D*H)	mm	680*640*1400	680*640*1400
		in	26.8*25.2*55.1	26.8*25.2*55.1
	Exterior Dimensions (W*D*H)	mm	780*840*1945	780*840*1945
		in	30.7*33.1*76.6	30.7*33.1*76.6
	Packing Dimensions (W*D*H)	mm	865*945*2090	865*945*2090
in		34.1*37.2*82.3	34.1*37.2*82.3	
Others	Container Load (20'/40'/40'H)	12/26/26	12/26/26	
	Certificate	CE	UL	