

Zip-IQ TT Test Tube Centrifuge

The LW Scientific Zip-IQ TT centrifuge is a 6-place test tube centrifuge for spinning blood, urine, and other fluids in 1.0ml to 15ml test tubes and microtubes. The unit is very small, conserving counter space in the lab, but also sturdy with suction-cupped feet for stability. Two programmable buttons allow you to set quick and easy speed and time selections. The RPM / RCF button toggles between displaying RPM or RCF (g-force). The digital controls allow speed and time to be adjusted with the touch of a finger and will show real-time speed and time remaining. The maintenance-free, brushless motor spins at 5,000rpm (2,500g) producing serum in as little as 5 minutes. Slow the speed to 2,000rpm (400g) to spin urines in 5 minutes. The auto-brake stops the rotor in 10 seconds, and the lid opens automatically upon completion. The Zip-IQ TT is the smart choice for any clinic or laboratory.

ADVANTAGES

- P1 and P2 programmable buttons for time and speed
- Small footprint conserves counter space
- Smooth, whisper-quiet operation
- Digital time and speed for accuracy
- 6-place angled rotor spins common 1.0ml-15ml test tubes and microtubes

FEATURES

- Angled 6-place test tube rotor with inserts 1.0ml to 15ml tubes)
- Max tube size 16.8mm diameter x 123mm tall
- Digital LCD displays speed, time, lid open/close
- Auto-lid-open at end of cycle
- Auto-brake stops rotor in 10 seconds
- Suction-cupped feet to prevent slipping
- Brushless maintenance-free motor
- Auto-switching AC adapter power supply
- Zero-RPM interlock – cannot open while spinning

SPECIFICATIONS

- Digital variable speed: 300-5,000rpm in steps of 100 rpm
- Maximum RCF= 2,500g
- Digital timer: 15 seconds to 99 minutes
- 100-240V 50/60Hz auto-switching power supply
- 24-volt brushless DC motor
- 53 dBA +/- 3 dBA @ 18"-24"

INCLUDES

- 6-place angled rotor for 7ml-15ml tubes
(Maximum: 16.9mm x 129mm)
- 6 black inserts for 5ml-6ml tubes
(Maximum: 13.0mm x 129mm)
- 6 white inserts for 3ml-4ml tubes
(Maximum: 13.0mm x 85mm)
- 6 green inserts for 1.0ml-2.0ml microtubes
(Maximum: 10.3mm x 47mm)
- 24 volt DC 4 amp AC power adapter
(100-240 volt AC 50/60Hz input)



Zip-IQ TT Test Tube Centrifuge

Model #	Description
ZIC-06AD-15T3	Digital, 6-place angled test tube rotor (0.5ml-15ml), 5,000 rpm, 0-lock, 100-240 volt

FASTEST - SMALLEST - QUIETEST

- Spins test tubes and microtubes
- Serum separations in as little as 5 minutes
- Two programmable buttons for quick and easy spins.

WEIGHT AND DIMS

Lid Open Height: 11.75" (298.45mm)
Height: 6.2" (158mm)
Length: 10.6" (270mm)
Width: 8.3" (212mm)
Weight: 9.9 lbs (4.5 kg)

Boxed Dimensions:

Height: 8.75" (203.2mm)
Length: 15" (381mm)
Width: 11" (279.4mm)
Weight: 12.25 lbs (5.56kg)



P 770.270.1394
F 770.270.2389

865 Marathon Parkway
Lawrenceville GA 30046

LWScientific.com