

Product Name:	PH-ABT-HC-12S
Description:	<p>Premier Pharmacy/Vaccine Solid Door Refrigerator</p> <p>12 Cu. Ft. capacity</p> <p>One swing solid door, self-closing, right hinged, not reversible</p> <p>Microprocessor Temperature Controller</p> <p>Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C)</p> <p>Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms</p> <p>Calibrated using a NIST traceable device, certificate included</p> <p>Adjustable temperature display in Celsius or Fahrenheit</p> <p>Audible and visual high/low temperature alarms</p> <p>2 probes; 1 in air and 1 in sample bottle</p> <p>Sensor error alarm</p> <p>Power failure alarm</p> <p>Resettable 1-point Min/Max History</p> <p>Remote alarm contacts</p> <p>Alarm validation (audible, visual, and remote alarm)</p> <p>Alarm mute with ring back</p> <p>5 total shelves, 3 adjustable plus 2 additional</p> <p>Vaccine storage power cord warning label</p> <p>Forced draft air circulation</p> <p>Keyed door lock</p> <p>LED interior lights are safety shielded and switch controlled</p> <p>Swivel Casters (3 ½")</p> <p>probe access port (⅜")</p> <p>White powder-coated steel exterior and interior</p> <p>Hydrocarbon, natural refrigerant (R290)</p> <p>Pharmacy refrigerator/freezer toolkit and temperature logs</p> <p>Two year parts and labor warranty, plus an additional three year compressor parts warranty</p> <p>Exterior dimensions: 25" W x 29 ¾" D x 65 ¾" H with casters; 62 ¼" H without casters</p> <p>Cycle defrost</p> <p>115V, 60 Hz, 3 Amps, 1/5 HP</p> <p>ETL listed</p> <p>Shipping weight: 227 lbs.</p>