

Product Name:	PH-ABT-HC-RFC9G-LH
Description:	<p>Premier Pharmacy/Vaccine Refrigerator & Freezer Combination 9 Cu. Ft. Capacity (4.6 Ref./4.2 Freezer) Two exterior swing doors (glass door refrigerator/solid door freezer), LEFT HINGED Microprocessor temperature controller, refrigerator and freezer Digital temperature display, refrigerator and freezer Adjustable operating temperature range: Refrigerator: 36°F – 46°F (2°C -8°C); Freezer: 5°F – -13°F (-15°C - -25°C) Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm Audible and visual high and low temperature alarms, refrigerator and freezer Remote alarm contacts, refrigerator and freezer 2 probes; 1 in air and 1 in sample bottle, in both Refrigerator and Freezer Adjustable operating temperature range: Refrigerator: 1°C – 10°C; Freezer: -15°C - -25°C 2 adjustable/1 fixed shelves refrigerator with guard rail on back to prevent product from being pushed against back wall/2 fixed shelves freezer Back wall evaporator cover, Refrigerator Forced draft circulation, Refrigerator Vaccine storage power cord warning label Keyed door locks Magnetic door gasket for positive seal Recessed door handle, freezer; heavy duty door handle, refrigerator Leveling legs Stacking kit LED interior light, Refrigerator Two probe access ports (3/8"); one, refrigerator/one, freezer White powder coated exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Exterior dimensions: 23 ¾" W x 25 ½"D x 66 ¾"H Two year parts and labor warranty, plus an additional three year compressor parts warranty Manual defrost freezer / cycle defrost refrigerator 115V, 60 Hz, 1.74 Amps Refrigerator, 1.5 Amps Freezer, 1/8 HP Refrigerator and Freezer UL/C-UL listed Shipping weight: 282 lbs.</p>

	*Please note this unit requires 2 outlets.
--	--