vacuum insulated) Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in sample bottle	Product Name:	PH-ABT-HC-S72G
72 Cu. Ft. Capacity Three swing glass doors, self-closing (energy efficient, double payacuum insulated) Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in sample bottle		
Calibrated using a NIST traceable device, certificate included Twelve adjustable shelves (adjustable in ½" increments) Vaccine storage power cord warning label Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Heavy duty door handles Swivel Casters (3 ½") LED interior lights are safety shielded and switch controlled Probe access port (¾") Powder coated steel white interior and exterior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerant (R290) Pharmacy refrigerator/freezer toolkit and temperature logs One year parts and labor warranty, plus an additional four year compressor parts warranty	Description:	Three swing glass doors, self-closing (energy efficient, double pane vacuum insulated) Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in sample bottle Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C) Calibrated using a NIST traceable device, certificate included Twelve adjustable shelves (adjustable in ½" increments) Vaccine storage power cord warning label Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Heavy duty door handles Swivel Casters (3 ½") LED interior lights are safety shielded and switch controlled Probe access port (¾") Powder coated steel white interior and exterior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerant (R290) Pharmacy refrigerator/freezer toolkit and temperature logs One year parts and labor warranty, plus an additional four year compressor parts warranty Exterior dimensions: 81" W x 34" D x 81 ¾" H with casters; 78 ¼" H without casters Cycle defrost 115V, 60 Hz, 7.5 Amps, 1/2 HP ETL listed