

Product Name:	PH-ABT-HC-UCBI-0404SS-LH
Description:	<p>Premier Pharmacy/Vaccine Undercounter Refrigerator Built-In – LEFT-HINGED</p> <p>4.5 Cu. Ft. Capacity</p> <p>One solid stainless steel swing door, left hinged</p> <p>Microprocessor temperature controller</p> <p>Digital temperature display</p> <p>Audible and visual high and low temperature alarms</p> <p>Remote alarm contacts</p> <p>2 probes; 1 in air and 1 in sample bottle</p> <p>Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C)</p> <p>Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm</p> <p>Three shelves (two adjustable/one fixed) with guard rail on back to prevent product from pushing against back wall</p> <p>Back wall evaporator cover</p> <p>Vaccine storage power cord warning label</p> <p>Forced draft circulation</p> <p>Recessed door handle</p> <p>Keyed door lock</p> <p>Magnetic door gasket for positive seal</p> <p>Leveling legs</p> <p>Probe access port (3/8")</p> <p>Stainless steel exterior</p> <p>High density urethane foam cabinet and door insulation</p> <p>HFC-free refrigerant (R600a), foam insulation and packaging</p> <p>Pharmacy refrigerator/freezer toolkit and temperature logs</p> <p>Two year parts and labor warranty</p> <p>Pyxis®, Omnicell® and AcuDose RX® compatible</p> <p>Exterior dimensions: 23 ¾"W x 24 ½"D x 33 ⅜"H</p> <p>Cycle defrost</p> <p>115V, 60 Hz, 1.74 Amps, 1/8 HP</p> <p>Energy Consumption 1.15 kWh/day</p> <p>UL/C-UL listed</p> <p>ENERGY STAR CERTIFIED</p> <p>Shipping weight: 135 lbs.</p>