| Product Name: | PH-ABT-HC-UCBI-0420A-LH  |
|---------------|--|
|               |  |
| Description:  | Built-In-LEFT HINGED   |
|               | 4.2 Cu. Ft. Capacity   |
|               | One solid swing door, left hinged, not reversible  |
|               | Microprocessor temperature controller  |
|               | Digital temperature display  |
|               | Audible and visual high and low temperature alarms   |
|               | 2 probes; 1 in air and 1 in glycol bottle  |
|               | Adjustable operating temperature range: 5°F – -13°F (-15°C – - 25°C)   |
|               | Auto defrost cycle every 6 hours, max air temp in empty freezer:   |
|               | +4.9°C; max air temp in loaded freezer: +0.6°C. Max sample temp in empty freezer: -9.1°C; max sample temp in loaded freezer: -11.2°C   |
|               | Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, "buffered" probe |
|               | in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm                  |
|               | Three adjustable shelves with guard rail on back to prevent product  |
|               | from being pushed against the back wall  |
|               | Vaccine storage power cord warning label   |
|               | Back wall evaporator cover   |
|               | Keyed door lock  |
|               | Heavy duty door handle   |
|               | Magnetic door gasket for positive seal   |
|               | Leveling legs  |
|               | Probe access port (3/8")   |
|               | Powder coat exterior   |
|               | High density urethane foam cabinet and door insulation   |
|               | HFC-free refrigerant (R290), foam insulation and packaging   |
|               | Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty   |
|               | Pyxis <sup>®</sup> , Omnicell <sup>®</sup> and AcuDose RX <sup>®</sup> compatible  |
|               | Exterior dimensions: 23 3/4" W x 24 1/2" D x 33 1/8"H  |
|               | Auto Defrost   |
|               | 115V, 60 Hz, 1.8 Amps 1/8 HP   |
|               | UL/C-UL listed   |
|               | Shipping weight: 143 lbs.  |
|               | DISCLAIMER: Auto defrost freezers incorporate an electric heater   |
|               | installed on the evaporator that assist in the removal of the frost and  |
|               | ice. Although the heater helps speed up the frost and ice removal, it  |
|               | can raise the temperatures within the freezer.   |