| Product Name: | PH-ABT-HC-UCFS-0104G |
|---------------|---|
| | |
| Description: | Premier Pharmacy/Vaccine Countertop Refrigerator Freestanding 1 Cu. Ft. Capacity |
| | One glass swing door, right hinged* |
| | Microprocessor temperature controller |
| | Digital temperature display |
| | Audible and visual high and low temperature alarms |
| | Remote alarm contacts |
| | 2 probes; 1 in air and 1 in sample bottle |
| | Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C) |
| | Temperature monitor device (TMD) complies with the current CDC |
| | guidelines, with 3 years certification of calibration, "buffered" probe |
| | in the product simulated solution, min/max memory, F/C switchable, |
| | field installable, and visual & audible temp alarm |
| | 2 adjustable shelves |
| | Back wall evaporator cover |
| | Vaccine storage power cord warning label |
| | Forced draft circulation |
| | Keyed door lock |
| | Integrated door handle |
| | Magnetic door gasket for positive seal |
| | Leveling legs |
| | LED interior light |
| | Probe access port (3/8") |
| | Powder coat exterior |
| | High density urethane foam cabinet and door insulation |
| | HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs |
| | Two year parts and labor warranty |
| | Pyxis [®] , Omnicell [®] and AcuDose RX [®] compatible |
| | Exterior dimensions: $17 \frac{1}{4}$ " W x 19 $\frac{1}{4}$ " D x 21 $\frac{1}{4}$ "H |
| | Note: This unit must have 4" clearance on sides and back for |
| | adequate ventilation |
| | Cycle defrost |
| | 115V, 60 Hz, .90 Amps, 1/8 HP |
| | Energy Consumption 0.71 kWh/day |
| | UL/C-UL listed |
| | ENERGY STAR CERTIFIED |
| | Shipping weight: 91 lbs. |
| | *This product is available left hinged, product number |
| | PH-ABT-HC-UCFS-0404G-LH |