

## PROLINE 882 RING ILLUMINATOR



### THE PROLINE 882 - 82mm RING ILLUMINATOR

The Proline 882 LED ringlights are designed with an inner and outerring populated by 80 high quality bright white LED's. The 82mm I.D. makes the PROLINE 882 ideal for mounting on large diameter optics.

The Proline 882 is designed with an inner and outer ring populated by 80 high quality, extremely bright, white LED's. The inner and outer rings of LED's are set at different angles to create uniform illumination across a wide range of working distances. Each ring and LED segment can be independently controlled using TechniQuips advanced eight segment LED controller. Dual dimming controls provide maximum color stability at all dimming levels. The ProLine 882 is specifically designed for mounting on large diameter optics and comes standard with an eight segment controller and universal power source for worldwide operation.

ProLine Series ringlights are designed and manufactured to the exacting standards that have made TechniQuip an industry leader in microscopy LED illumination. Manufactured in TechniQuip's own Pleasanton, California factory, the ProLine 882 is backed by the great service and warranty that have made TechniQuip the first choice for OEM equipment, semiconductor fabs, machine vision, laboratories, and other "mission critical" applications.

### Key Features

- ▶ 80 Powerful high precision aligned LEDs
- ▶ Choice of Daylight, Cool White, Warm White or UV LEDs
- ▶ Supplied with 8 quadrant controller and auto voltage sensing power supply
- ▶ Machined aluminum alloy housing for durability
- ▶ Supplied with 3 soft tip mounting screws
- ▶ 2 Fully adjustable dimming control
- ▶ 360 Degree shadow-free illumination
- ▶ Silent vibration free operation
- ▶ Instant on performance
- ▶ Standard model fits 1.25"-2.6" (66mm) lenses
- ▶ Adaptable for machine vision applications
- ▶ Larger diameter model (P882) fits 82mm (3.23") lenses (Designed for NIKON's new objective lenses)
- ▶ HDMI cable included - Connects controller to ring

# TECHNICAL SPECIFICATIONS: PROLINE 882



|  |                    |
|--|--------------------|
| Number of LEDs   | 80                 |
| Inside Ring Diameter                                       | 3.23 inch (82 mm)  |
| Outside Ring Diameter                                      | 4.11 inch (105 mm) |
| Height   | 2.165 inch (55 mm) |
| Cable Length   | 6 feet             |
| Minimum Working Distance (Dark Spot Disappears)            | 3.5 inch (88.9 mm) |
| Ideal Working Distance (Max Illuminance/Even illumination) | 3.5 inch (88 mm)   |
| Maximum (Effective) Working Distance                       | 5.0 inch (127 mm)  |

## SHIPPED READY TO USE

The ProLine 40 consists of three components:

One LED 40 Ring, a 4 quadrant controller and one AC/DC Switching Adapter:

Input: 100-240V - 50/60 Hz, 0.5A  
Output: 24V -0.75A, 18W Maximum

## ESD MODELS

Proprietary metal finishing provides a superior ESD finish

Machined aluminum alloy controller

Shielded interconnect cable

## CUSTOM SOLUTIONS IN LIGHTING

TechniQuip offers custom solutions in precision lighting devices, LED ring lights, LED light sources, halogen light sources, fiber optic rings, fiber optic cables, goose-necks, cross-hair generators, optical inspection systems, CCD video cameras, optics and adapters for all of your microscope needs.

Call or E-mail us today if you would like discuss our specialized turnkey services in design, R&D, and production. We guarantee all of our products. Techniquip: A proud tradition of sales and service for more than 40 years.

*Techniquip: A proud tradition of sales and service for more than 40 years.*



# PROLINE 882 - 66MM RING MODELS

| COMMON       | MODELS  |
|--------------|---|
| P882-DS8-EXW | ProLine, 82mm I.D., Daylight, Standard Working Distance, 8 Segment Controller, No ESD, USA Plug |
| P882-CS8-EXW | ProLine, 82mm I.D., Daylight, Standard Working Distance, 8 Segment Controller, No ESD, USA Plug |
| P882-WS8-EXW | ProLine, 82mm I.D., Daylight, Standard Working Distance, 8 Segment Controller, No ESD, USA Plug |

  

| ESD               | MODELS  |
|-------------------|---|
| P882-ZS8-XXW-UV   | ProLine, 82mm I.D., Daylight, Standard Working Distance, 8 Segment Controller, No ESD, USA Plug |
| P882-ZS8-XXW-UV-D | ProLine, 82mm I.D., Daylight, Standard Working Distance, 8 Segment Controller, No ESD, USA Plug |
| P882-ZS8-XXW-D-UV | ProLine, 82mm I.D., Daylight, Standard Working Distance, 8 Segment Controller, No ESD, USA Plug |

  

| ESD             | MODELS  |
|-----------------|---|
| P882DS8XXW-UV   | ProLine, 82mm I.D., Daylight, Standard Working Distance, 8 Segment Controller, No ESD, USA Plug |
| P882CS8XXW-UV-D | ProLine, 82mm I.D., Daylight, Standard Working Distance, 8 Segment Controller, No ESD, USA Plug |
| P882WS8XXW-D-UV | ProLine, 82mm I.D., Daylight, Standard Working Distance, 8 Segment Controller, No ESD, USA Plug |

  

| UV WITH ESD     | MODELS  |
|-----------------|---|
| P882ZS8EXW-UV   | ProLine, 82mm I.D., 80 Ultraviolet LED's, Standard Working Distance, 8 Segment Controller, ESD, USA Plug                                  |
| P882ZS8EXW-UV-D | ProLine, 82 mm I.D., 40 Inner Ring UV LED's, 40 Outer ring Daylight LED's, Standard Working Distance, 8 Segment Controller, ESD, USA Plug |
| P882ZS8EXW-D-UV | ProLine, 82 mm I.D., 40 Outer Ring UV LED's, 40 Inner Ring Daylight LED's, Standard Working Distance, 8 Segment Controller, ESD, USA Plug |



# PROLINE 882 SELECTION GUIDE

- P** — **Model Name**  
P8 = 80 LED ProLine
- 8** —
- 6** — **Inside diameter (mm)**  
66 = 66mm (80 LED ProLine)  
Before any reducing adapters are added)
- 6** —
- D** — **Corrected Color Temperature**  
D = Daylight ~ 5000 -9000 CCT  
C = Cool White ~ 4000-4900 CCT  
W= Warm White ~ 2750 - 3400 CCT  
Z = UV Custom  
(See Last Item In Selection Guide)
- S** — **Beam Angle**  
S = Standard (Short and Long W.D.)
- 8** — **Segment Control**  
8 = 8 (Inner and outer 90 degree segments)
- X** — **ESD Compliant**  
X = None  
E = ESD Compliant
- X** — **Remote Control**  
X = Not Available
- W** — **Power Converter**  
W = Wall type with USA Plug (100-240 VAC,50-60Hz, 0.5A)  
U = International Desk Top Auto Voltage Sensing Power Supply
- W** — **Optional**  
Specify Power Cord Option When Ordering International Table Top Power Supply:  
K=USA, A= Euro, C= Australia, D=UK, H= Israel, L= Switzerland
- X** — **Custom (Specify Inner and Outer Ring and Color Temperature)**  
UV = 80 UV LED's
- X** — UV-D = 40 Inner Ring UV, 40 Outer Ring (D)Daylight, (W) Warm White or (C) Cool White. (For Short W.D. UV Work)
- X** — D-UV = 40 Inner Ring (D) Daylight, (W) Warm White or (C)Cool White, 40 Outer Ring UV. (For Long W.D. UV Work)



(W) USA Wall Mount Switching

- Plug-In-Power Supply
- 25% More Efficient
- 50% Smaller
- 70% Lighter

Than Traditional  
Linear Power Supplies

