

SCIOLOGEX MX-M Microplate Mixer is used for holding single or double microplates. The compact shape of MX-M Microplate Mixer occupies less bench-space. It is widely used in life sciences including microbiology, cell and molecular biology, immunology and biotechnology.

MX-M Microplate Mixers

Features:

- A wide speed range from 100 to 1500rpm
- Used for various mixing applications with optional adapters
- Maintenance-free brushless DC motor



Brushless DC motor



Wide range of accessories



Universal top plate

Used with tube adapters

Cat. No.18900067



Tube adapter

for 48 holes test tubes, Ø6mm

Cat. No.18900020



Tube adapter

for 15 holes test tubes, Ø10mm

Cat. No.18900021



Tube adapter

for 12 holes test tubes, Ø12mm

Cat. No.18900022



Tube adapter

for 8 holes test tubes, Ø16mm

Cat. No.18900023



Tube adapter

for 8 holes test tubes, Ø20mm

Cat. No.18900024



MXM-116

Double microplate clamps

Cat. No.18900079

Specifications

Shaking movement	Orbital
Orbital diameter	4.5mm
Max. shaking weight (with accessory)	0.5kg
Motor type	Brushless DC motor
Motor rating input	18W
Motor rating output	10W
Speed range	Single microplate: 0-1500rpm Double microplate: 0-1000rpm
Speed display	Scale
Voltage	100-240V,50/60Hz
Power	20W
Dimension	260×150×80mm
Weight	3kg
Permissible ambient temperature and humidity	5-40°C,80%RH
Protection class	IP21

MX-M

Shaking movement	Orbital
Orbital diameter	4.5mm
Max. shaking weight (with accessory)	0.5kg
Motor type	Brushless DC motor
Motor rating input	18W
Motor rating output	10W
Speed range	Single microplate: 0-1500rpm Double microplate: 0-1000rpm
Speed display	Scale
Voltage	100-240V,50/60Hz
Power	20W
Dimension	260×150×80mm
Weight	3kg
Permissible ambient temperature and humidity	5-40°C,80%RH
Protection class	IP21