

## *SO-LOW STABILITY CHAMBER MODEL SCN4-52GD*

**49 Cubic Ft. Upright – Temperature Range: 20°C to 60°C / Glass Doors**

### **Specifications:**

|                      |                       |
|----------------------|-----------------------|
| * Capacity           | 49 cubic ft.          |
| * Temperature Range  | 20°C to 60°C          |
| * Dimensions         |                       |
| * Exterior w x d x h | 54" x 35.875" x 81.5" |
| * Interior w x d x h | 49" x 25.5" x 59"     |

### **Features:**

- Glass Doors
- Casters
- Controller Information:
- Proportional integral derivative (PID) controller with graphic display
- Programmable ramp and soak
- Process phase graphic animations
- USB data port
- RS-485 communication (MODBUS-RTU)
- Real time clock
- Battery backup
- Event logs: 100
- Visual alarm indicator
- Audible alarm indicator
- Process phase specific temp alarm
- Power failure alarm
- Sensor failure alarm
- Designed for pharmaceutical, biological research, Stability, shelf-life testing, plant growth  
Ducted airflow and plenum system optimize air flow and Ensure tight temperature uniformity.
- Control accuracies of 0.1°C control with +/-0.5°C uniformity
- User friendly Programmable Logic Microprocessor control
- Stainless Steel Interior standard
- White Painted Exterior
- Shipping Weight - 594 lbs.
- 115/60/1 12 Amps, 1/3 HP
- Warranty-(Domestic)  
1 ½ years parts and labor.  
Compressors additional 3 ½ years, no labor.

Specifications subject to change without notice

