

## **STORM3000** ECONOMICAL CHEMICAL-RESISTANT DIAPHRAGM VACUUM PUMP

The **STORM3000** economical chemical-resistant diaphragm vacuum pump is constructed from quality parts, manufactured in the USA and offered at an affordable price. This Laboratory Vacuum pump is library-quiet - the noise level is only ~ 54 dB small, durable, and chemical resistant! The **STORM3000** is nearly maintenance-free because of the PTFE coated surfaces, PTFE membrane, stainless steel valves and oil-free design. The pump features a vacuum regulator with gauge to adjust and monitor vacuum level. The **STORM3000** is a 20 psi continuous duty pump.

Air Flow Rate (lpm)	CFM (L/min) @ 60 Hz 0.7 (20)	
Maximum Vacuum, Hg	22"	
Ultimate Pressure, Torr (mbar)	190 (253)	
Tubing Needed, I.D.	1/4"	
Cord Supplies	North American 115V Plug	
Motor H.P.	1/7	
Usage Hours	15,000	
Motor Voltage & Frequency	115V, 60Hz, 1 Phase	
Motor Amps	1.5	
Overall Pump Dimensions	6.8"L x 7.3"W x 8.3"H	
Shipping Dimensions	14"L x 14"W x 14"H	
Weight	7.5 lbs.	
Shipping Weight	10 lbs.	
Certification	UL Recognized	
Warranty	One Year Warranty	





Regulator Kit Includes:

- Dial Pressure gauge
- Hand Knob Control
- 1/4" O.D. Hose barb
- 1/8" NPT Exhaust Adapter
- Built in Silencer

Instruction sheet for installation on both pumps.

CATALOG NO.	DESCRIPTION	PRICE
STM3000	STORM3000 Economical Chemical Resistant Diaphragm Vacuum Pump 115V, 60Hz	\$655.00
STM3000K-01	Service Kit - Diaphragm Replacement Parts STM3000	\$62.00
STM3000K-03	Service Kit - Major Rebuild Parts STM3000	\$334.00
STM2500K-04	Service Kit - Rubber Suction Cup Feet	\$117.00
STM3500K-06	Pressure Regulator Kit Assembly	\$220.00





## **STORM5000** CHEMICAL-RESISTANT DIAPHRAGM VACUUM PUMP

The **STORM5000** (115V) and **STORM5000C-02** (230V) Chemical Resistant Diaphragm Vacuum Pumps are durable and chemical resistant. All contact surfaces are PTFE coated. Both include an inlet trap and vacuum regulator, and are a perfect choice for vacuum filtration, desiccation, and other mid-range vacuum applications. The **STORM5000** and **STORM5000C-02** are resistant to bleach and acetone vapors allowing them to be used with cell culture decontamination protocols. The **STORM5000** and **STORM5000C-02** are a 20 psi continuous duty pump.

Air Flow Rate (lpm)	CFM (L/min) @ 60 Hz 1.3 (37) CFM (L/min) @ 50 Hz 1.1 (31)	
Maximum Vacuum, Hg	24"	
Ultimate Pressure, Torr (mbar)	150 (200)	
Tubing Needed, I.D.	1/4"	
Cord Supplies	North American 115V Plug or North American 230V and 230V European Shuko	
Motor H.P.	1/5	
Usage Hours	15,000	
Motor Voltage & Frequency	115V, 60Hz, 1 Phase	
Motor Amps	3.5	
Overall Pump Dimensions	8.75"L x 5.0"W x 8.75"H	
Shipping Dimensions	20" L x 16"W x 14"H	
Weight	13 lbs.	
Shipping Weight	16 lbs.	
Certification	UL Recognized	
Warranty	One Year Warranty	



## PRESSURE REGULATOR KIT ASSEMBLY

Regulator Kit Includes:

- Dial Pressure gauge
- Hand Knob Control
- 1/4" O.D. Hose barb
- 1/8" NPT Exhaust Adapter
- Built in Silencer

Instruction sheet for installation on both pumps.

CATALOG NO.	DESCRIPTION	PRICE
STM5000	STORM5000 Chemical Resistant Diaphragm Vacuum Pump 115V, 60Hz	\$1065.00
STM5000C	STORM5000C Chemical Resistant Diaphragm Vacuum Pump 230V, 50 Hz	\$1207.00
STM5000K-01	Service Kit - Diaphragm Replacement Parts STM5000	\$120.00
STM5000K-03	Service Kit - Major Rebuild Parts STM5000	\$309.00
STM2500K-04	Service Kit - Rubber Suction Cup Feet	\$117.00
STM3500K-06	Pressure Regulator Kit Assembly	\$220.00

