

▶ Features

- · It is an analytical instrument with high precision and photometric stability.
- · It has a menu of settings and self-evaluation
- $\cdot \ \mathsf{Additional} \ \mathsf{option} \ \mathsf{for} \ \mathsf{connection} \ \mathsf{to} \ \mathsf{operation} \ \mathsf{software} \ \mathsf{and} \ \mathsf{data} \ \mathsf{download} \ \mathsf{(not} \ \mathsf{included)}.$
- · Storage of all your data on computer equipment.

▶ Functions

- · Measurement of absorbance. · Transmittance measurement
- $\cdot \ \mathsf{Quantitative} \ \mathsf{analysis} \ \mathsf{using} \ \mathsf{concentration} \ \mathsf{curves}. \ \mathsf{\cdot Measurement} \ \mathsf{of} \ \mathsf{nucleic} \ \mathsf{acid} \ \mathsf{purity} \ \mathsf{and} \ \mathsf{concentration}$
- · Wavelength and protein scanning.
- \cdot 3D spectrograms

Software

 \cdot Handling and operation of the spectrophotometer, concentration curves, kinetic analysis, wavelength scanning and 3D spectrograms; analysis of purity, concentration of nucleic acids, proteins

► Accesories included

· Software Meta Spec Pro.

TECHINICAL DATA	
Model	VE-5600UV PC
Wavelength range	190 – 1100 nm.
Bandwidth	2 nm.
Wavelength accuracy	± 0.8 nm
Wavelength repeatability	1 nm.
Calibration	Automatic.
Diffused light	≤0.05 % T a 220nm y 360 nm
Photometric repeatability	± 0.2 % T
Photometric precision	± 0.3 % T
Stability	0.002 A / h a 500nm
Detector	Silicon photodiode.
Light source	Halogen / Tungsten (Visible) and Deuterium (Ultraviolet) Lamp
Data interfaces	USB A / B port, RS-232 port for printer.
Screen	LCD.
System software	Meta Spec Pro version 2.2: Core i3 or higher processor, CD
	reader, USB 2.0 interface, RAM memory greater than 2.0 GB,
	Windows XP, 7, 8 and 10. Includes access key and installation
	CD.
Dimensions	460 x 380 x 230 mm
Power Supply	110-220V, 50/60 Hz, 3.15 A, AC Adapter.
Warranty	1 year.



- www.velab.net
- **+**1 956.429.3410
- ▶ sales@velab.net
- ▶ 1431 W Polk Ave, Pharr Texas