



VE-BFS150

VE-BFS150L

VE-BFS300L



► Features

- RS232 interface.
- Full Range tare function.
- Auto shut-off.
- Removable display

► Standard Functions

- Weighing.
- Hold Function.

► Accessories Included

- Power adaptor.
- Wall mount.

► TECHNICAL DATA

Model	VE-BFS150	VE-BFS150L	VE-BFS300L
Capacity	150kg / 330lb	150kg / 330lb	300kg / 660lb
Readability	0.05kg / 0.2lb	0.05kg / 0.2lb	0.1kg / 0.2lb
Repeatability	±0.05kg / 0.2lb	±0.05kg / 0.2lb	±0.1kg / 0.2lb
Linearity	±0.1kg / 0.4lb	±0.1kg / 0.4lb	±0.2kg / 0.5lb
Weighing Units	kg, lb, oz		
Calibration	External		
Pan Size	310 x 300mm / 12.2" x 11.8"	950x500mm / 37.4"x19.7"	
Stabilization Time	2 seconds		
Interface	RS232		
Display	LCD, digit height 25mm / 1"		
Housing	Metal housing and stainless steel pan		
Operating Environment	5° to 40°C / 41° to 104°		
Overall Dimensions	315 x 325 x 55mm	950x500x65mm / 37.4" x 19.7" x 2.6"	
Power Supply	110/240V, 50/60 Hz AC Adapter and 6MAA batteries (not included)		
Net Weight	5.5 kg / 12lb	16 kg / 35.2 lb	
Warranty	1 year		