



VE-LCB6

VE-LCB12

## **Features**

- · High contrast LCD screen.
- · Robust ABS housing
- · Leveling feet.

















- - · Multiple weighing units (5 total).

- · Internal rechargeable battery.
- · Large stainless steel pan.
- · RS232 interface.

## **Standard Functions**

- · Weighing.
- · Parts counting.

- · Checkweighing
- · Percentage weighing.

## **Accesories Included**

· Clear protective cover.

· RS232 cable.

TECHNICAL DATA			
Model	VE-LCB6	VE-LCB12	
Capacity	6 kg / 12 lb	12 kg / 25 lb	
Readability	0.1 g / 0.0002 lb	0.1 g / 0.0002 lb	
Repeatability	±0.1 g	±0.1 g	
Linearity	±0.2 g	±0.2 g	
Weighing Units	g, kg, oz, ozt, lb. External. 186 x 186mm / 7.3" x 7.3" 1.5 seconds. RS232 LCD, digit height 25 mm / 1". ABS plastic.		
Calibration			
Pan Size			
Stabilization Time			
Interface			
Display			
Housing			
Operating Environment	10° to 30°C / 50° to 85°F / Humidity 20% - 80%		

10° to 30°C / 50° to 85°F / Humidity 20% - 80%

110/240V, 50/60 Hz AC Adapter and rechargeable battery.

300 x 200 x 91mm / 12" x 8" x 3.6.



Overall Dimensions

**Power Supply** 

Net Weight

Warranty

www.velab.net

1 year.

2.4kg / 5.3lb

- **+**1 956.429.3410
- ► sales@velab.net
- ▶ 1431 W Polk Ave, Pharr Texas