Product Name:	ABT-MFP-15-C
Description:	15 Cu. Ft. capacity One solid door Microprocessor temperature controller: Adjustable operating temperature range: -15°C – -25°C Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms Sample simulated digital temperature display: .1C resolution, convertible to display temperatures in Celsius or Fahrenheit Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts LED Interior light Two removable baskets Swivel casters (2 ¾") Keyed door lock Magnetic door gasket for positive seal White cabinet and lid One probe access port (3/8") High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging One-year parts and labor warranty, plus an additional four year compressor parts warranty Exterior dimensions: 56" W x 29 ½"D x 35 1/8"H with casters; 32 3/8" without casters (Height with hinged door open 90° is 62 ½") Manual defrost 115V, 60 Hz, 5 Amps, 1/4 HP
	Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts LED Interior light Two removable baskets Swivel casters (2 ¾") Keyed door lock Magnetic door gasket for positive seal White cabinet and lid One probe access port (3/8") High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging One-year parts and labor warranty, plus an additional four year compressor parts warranty Exterior dimensions: 56" W x 29 ½"D x 35 1/8"H with casters; 32 3/8" without casters (Height with hinged door open 90° is 62 ½") Manual defrost