

ARS2PV456LHD



22.25" x 18.5" x 23.25" (H x W x D)

Performance series Pharma-Vac 2 cu.ft. all-refrigerator certified to NSF/ANSI 456 Vaccine Storage Standard

Highlights:

Certified to NSF/ANSI 456 Vaccine Storage Standard

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Product Features:

Certified to NSF/ANSI 456 Vaccine Storage Standard Designed and tested to comply with the new NSF Vaccine Storage Standard

| | |
|---|--|
| Purpose-built design | Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines |
| +/-1°C Variation | The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period |
| Certificate of calibration included | 2-year calibration certificate included for your records |
| Adjustable temperature | Intuitive controls let you adjust the interior temperature between +2 to +8°C |
| Temperature alarm | Visual and audible alarms alert if the interior temperature rises or falls out of set range |
| Remote alarm contacts | Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit) |
| Automatic defrost with adjustable cycle defrost | Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup |
| Access port | Includes a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to user-provided monitoring equipment |

ARS2PV456LHD Specifications:

Overview

| | |
|----------------------------|--------------------|
| Height of Cabinet | 22.25" (57 cm) |
| Width | 18.5" (47 cm) |
| Width with Door Open | 18.88" (48 cm) |
| Depth | 23.25" (59 cm) |
| Depth with Handle | 24.75" (63 cm) |
| Depth with door at 90° | 42.5" (108 cm) |
| Capacity | 1.94 cu.ft. (55 L) |
| Defrost Type | Automatic |
| Door | White |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S to NSF 456 |
| Amps | 0.6 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 80.0 lbs. (36 kg) |
| Parts & Labor Warranty | 2 Years |
| Compressor Warranty | 5 Years |
| UPC | 761101107042 |

Refrigerator Features

| | |
|--------------------|----------|
| Door Swing | LHD |
| Reversible | No |
| Shelf Type | Wire |
| Shelf Qty | 2 |
| Adjustable Shelves | Yes |
| Thermostat Type | Digital |
| Fan Type | Interior |
| Refrigerant Type | R600a |
| Refrigerant Amount | 0.84oz. |
| High Side PSI | 280.0 |
| Low Side PSI | 90.0 |
| Interior Light | Yes |
| Temperature Range | 2 to 8°C |
| Sound Level | 44.2 dB |

Dimensions

| | |
|-----------------|----------------|
| Interior Height | 16.5" (42 cm) |
| Interior Width | 15.25" (39 cm) |

| | |
|------------------------|----------------|
| Interior Depth | 15.75" (40 cm) |
| Compressor Step Height | 8.25" (21 cm) |
| Compressor Step Width | 15.25" (39 cm) |
| Compressor Step Depth | 4.25" (11 cm) |

