

ARS3PV-ADA305AFSTACK



66" x 19.75" x 22.5" (H x W x D)

Stacked combination of ARS3PV automatic defrost vaccine refrigerator with antimicrobial silver-ion handle and ADA305AF manual defrost vaccine freezer, both with hospital grade cords with 'green dot' plugs

Highlights:

Independent refrigerator and freezer storage in one slim-fitting footprint for space-challenged facilities

ADA305AF freezer has a medical grade design to function at lower temperatures (-25°C) than standard residential units

Easy temperature management with intelligent microprocessor digital temperature controller (refrigerator) and digital thermostat located in the kickplate (freezer)

Product Features:

Space-saving design	Allows you to create a full refrigerator-freezer with independent controls in a slim-fitting footprint
Easy assembly	Unit ships in three boxes for customer to install the StackRack on the bottom freezer and place and secure the refrigerator on top
+/-1°C Variation (refrigerator)	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period
-25°C capable (freezer)	Low temperature operation ideal for vaccines, pharmaceuticals, and other sensitive materials
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2 to +8°C (refrigerator) and -25° to -15°C (freezer)
Antimicrobial silver ion-coated handle (refrigerator)	Powder-coated handle with naturally occurring silver ions to help reduce germ spread
Temperature alarms	Visual and audible alarms alert if the interior temperature rises or falls out of set range
Automatic defrost with adjustable cycle defrost (refrigerator)	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup
Remote alarm contacts (refrigerator)	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)
ACCUCOLD DIVISION, FELIX STORCH, INC. ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799	
 info@accucold.com  www.accucold.com	

ARS3PV-ADA305AFSTACK Specifications:

Overview	
Nominal Height	66.0" (168 cm)
Height of Cabinet	66.0" (168 cm)
Nominal Width	20.0" (51 cm)
Width	19.75" (50 cm)
Width with Door Open	20.25" (51 cm)
Nominal Depth	23.0" (58 cm)
Depth	22.5" (57 cm)
Depth with Handle	24.38" (62 cm)
Depth with door at 90°	40.0" (102 cm)
Capacity	5.47 cu.ft. (155 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	1.7
Voltage/Frequency	115 V AC/60 Hz
Weight	151.0 lbs. (68 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101078632

Refrigerator-Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Adjustable Shelves	Yes
Interior Drawers	Yes
Drawer Qty	3
Interior Light	Yes
Refrigerator - Interior Height	28.38" (72 cm)
Refrigerator - Interior Width	15.25" (39 cm)
Refrigerator - Interior Depth	11.75" (30 cm)
Refrigerator - Capacity	3.0 cu.ft
Refrigerator - Shelf Type	Wire
Refrigerator - Shelf Qty	4
Refrigerator - Temperature Range	2 to 8°C

Refrigerator - Refrigerant Type	R600a
Refrigerator - Refrigerant Amount	1.06 oz.
Freezer - Interior Height	23.75" (60 cm)
Freezer - Interior Width	14.5" (37 cm)
Freezer - Interior Depth	17.0" (43 cm)
Freezer - Capacity	2.47 cu.ft
Freezer - Shelf Type	Drawers
Freezer - Shelf Qty	3
Thermostat Type	Digital
Fan Type	Interior
Level Legs	2
Freezer - Temperature Range	-25° to -15°C
Freezer - Refrigerant Type	R600a
Freezer - Refrigerant Amount	1.34 oz.

