

# VT65MLBIMEDADA



32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant built-in undercounter all-freezer capable of -25° C operation; includes audible alarm, lock, and hospital grade plug

### Highlights:

Flexible design allows built-in or freestanding use in 24" wide spaces

32" height for use in ADA compliant settings

-25° C operation for safe storage of temperature sensitive materials

### Product Features:

ADA compliant	32" high to fit under lower ADA compliant counters
Built-in capable	Make the best use of space by installing your appliance under the counter
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety
Factory installed lock	Keyed lock for secure interior
-25°C capable	Low temperature capability ideal for certain sensitive items
High temperature alarm	Warns of temperature fluctuations and includes an external temperature readout on the door
Manual defrost	Efficient performance with reliable temperature stability
Three removable storage baskets	Conveniently organize your items while keeping the temperature stable when the door is opened
Access port	Unit comes with a factory installed probe hole for users to connect their own monitoring equipment

## VT65MLBIMEDADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	24.25" (62 cm)
Depth with door at 90°	45.13" (115 cm)
Capacity	3.2 cu.ft. (91 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	105.0 lbs. (48 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101044705
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Thermostat Type	Digital
Fan Type	Exterior
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	17.5" (44 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	-12°C to -25°C

