

VT65MLCSS



33.5" x 23.75" x 23.5" (H x W x D)

Built-in medical all-freezer capable of -25° C operation in complete stainless steel with front lock; built-in or freestanding capable

Highlights:

Complete stainless steel exterior for luxury built to last

Factory-installed lock provides security you can count on

-25° C operation for safe storage of temperature sensitive materials

Product Features:

Slim undercounter dimensions	Less than 24 inches wide to fit tight spaces
Built-in capable	Make the best use of space by installing your appliance under the counter and flush with other cabinets
Fully finished cabinet	Allows the freezer to be used freestanding
Complete stainless steel exterior	Durable design with lasting elegance
Professional towel bar handle	A curved stainless steel handle provides generous room for a comfortable grip
Factory installed lock	Keep contents secure with a key lock on the door
-25° C capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials
Manual defrost	No temperature fluctuations with a manual defrost system that keeps the cold inside
Three removable storage baskets	Conveniently organize your items while keeping the temperature stable when the door is opened

VT65MLCSS Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.75" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.5" (65 cm)
Depth with door at 90°	45.25" (115 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Amps	1.3
Weight	105.0 lbs. (48 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101030845
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Height Adjustable	1
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Thermostat Type	Dial
Fan Type	Exterior
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Level Legs	4
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.0" (15 cm)
Compressor Step Width	17.75" (45 cm)
Compressor Step Depth	6.0" (15 cm)
Temperature Range	-12°C to -25°C

