accuc@ld

VT65MLMEDADA



32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant 24" wide all-freezer for freestanding use capable of -25° C operation; includes audible alarm, lock, and hospital grade plug

Highlights:

32" height for use in settings following ADA guidelines

Factory installed lock provides security you can count on

-25° C operation for safe storage of temperature sensitive materials

Product Features:

ADA compliant	32" height for use in settings following ADA guidelines	
Factory installed lock	Keyed lock for secure interior	
-25°C capable	Low temperature capability ideal for certain sensitive items	
High temperature alarm	Warns of temperature fluctuations and includes an external temperature readout on the door	
Manual defrost	Efficient performance with reliable temperature stability	
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety	
Pull-out drawers	Clear baskets for convenient and separated storage	
Access port	Unit comes with a factory installed probe hole for users to connect their own monitoring equipment	
Digital thermostat	Electronic controls located in the front kickplate for easy and intuitive temperature management	





accuc@ld

VT65MLMEDADA Specifications:

Overview		
Height of Cabinet	32.0" (81 cm)	
Height to Hinge Cap	32.25" (82 cm)	
Width	23.63" (60 cm)	
Depth	23.5" (60 cm)	
Depth with Handle	24.25" (62 cm)	
Depth with door at 90°	45.0" (114 cm)	
Capacity	3.2 cu.ft. (91 L)	
Defrost Type	Manual	
Door	White	
Cabinet	White	
US Electrical Safety	UL	
Canadian Electrical Safety	ULC	
Amps	1.3	
Voltage/Frequency	115 V AC/60 Hz	
Weight	105.0 lbs. (48 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
UPC	761101038391	
Freezer		
Door Swing	RHD	
Reversible	Factory Reversible	
Interior Height	24.25" (62 cm)	
Interior Width	17.75" (45 cm)	
Interior Depth	16.5" (42 cm)	
Thermostat Type	Digital	
Refrigerant Type	R134a	
Refrigerant Amount	2.7 oz.	
High Side PSI	235.0	
Low Side PSI	70.0	
Interior Drawers	Yes	
Drawers Qty	3	
Compressor Step Height	6.5" (17 cm)	
Compressor Step Width	17.5" (44 cm)	
Compressor Step Depth	5.5" (14 cm)	
	-12°C to -25°C	

