Description: White Diamond Series Countertop Refrigerator Freestanding-LEFT HINGED 1 Cu. Ft. Capacity One glass swing door, left hinged Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes: 1 in air and 1 in glycol bottle	Product Name:	PR011WWGLH/0
HINGED 1 Cu. Ft. Capacity One glass swing door, left hinged Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts		
Adjustable operating temperature range: 1°C – 10°C 2 adjustable shelves Back wall evaporator cover Forced draft circulation Keyed door lock Integrated door handle Magnetic door gasket for positive seal Leveling legs LED interior light Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Three year parts and labor warranty, plus an additional two year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 17 ¼"W x 19 ¼"D x 21 ¼"H Note: This unit must have 4" clearance on sides and back for adequate ventilation Cycle defrost 115V, 60 Hz, .90 Amps, 1/8 HP ENERGY STAR CERTIFIED UL/C-UL listed Shipping weight: 91 lbs.	Description:	HINGED 1 Cu. Ft. Capacity One glass swing door, left hinged Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: 1°C – 10°C 2 adjustable shelves Back wall evaporator cover Forced draft circulation Keyed door lock Integrated door handle Magnetic door gasket for positive seal Leveling legs LED interior light Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Three year parts and labor warranty, plus an additional two year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 17 ¼"W x 19 ¼"D x 21 ½"H Note: This unit must have 4" clearance on sides and back for adequate ventilation Cycle defrost 115V, 60 Hz, .90 Amps, 1/8 HP ENERGY STAR CERTIFIED UL/C-UL listed