



designed for scientists



MultiDrive control BT Package

/// Data Sheet

Crushing without cross-contamination - this is possible with the MultiDrive control package including autoclavable disposable tubes BT 250 and the required TC 1 protective housing for dry samples.

BT 250 is a disposable tube with a cross-shaped stainless steel beater and flow breakers. The plastic blending tube can be autoclaved. This effectively prevents cross-contamination even if it is used multiple times. An integrated RFID chip simultaneously stores and limits the lifespan of the blending tube. 5 spare seals are included in the scope of delivery. By replacing the seal, the service life of the blending tube can be extended. The disposable tube can only be operated with the TC 1 protective housing which is also included in the scope of delivery.



designed for scientists

MultiDrive universal crusher can perform a wide range of crushing tasks involving coarse and fine crushing, thanks to the variety of vessels available. There is a USB interface available for easy actuation and documentation respectively.

High performance

Excellent crushing performance is guaranteed by a combination of variable rotational speeds, ranging from 3000 rpm to 20 000 rpm, and a 1000 Watt output.

Interval operation

The option of interval programming is simple to activate at the press of a button. Interval operation is an asset during the coarse crushing of hard samples or for extra thorough blending.

Integrated cooling

A cooling system is integrated in the milling cup, which allows indirect heat dissipation. Thus, coolant and sample remain separate.

TFT-display

A clear TFT-display guarantees user-friendly operation.

Temperature measurement

MultiDrive control offers temperature measurement and vessel recognition using RFID. A temperature limit can be set for temperature-sensitive materials, or for specific planned reactions to protect against overheating.

Weighing function

The weighing function is also integrated into the user-friendly workflow of the IKA MultiDrive control. Weighing is performed before crushing using the same mixing cup, so that no transfer of contents is required.

Technical Data

Process type	batch
Operating principle	cutting/impact/blending/dispersing
Motor rating input [W]	1000
Motor rating output [W]	800
Speed range [rpm]	3000 - 20000
Speed deviation [%]	±5
Power-ON time [min]	5
Power-OFF time [min]	10
Motor principle	Brushless DC
Display	TFT
RFID reader/writer unit	yes
Temperature display	yes
Temperature measurement resolution [K]	0.1
Accuracy of temperature measurement [K]	±1
Temperature limit min. [°C]	-50
Temperature limit max. [°C]	120
Monitoring maintain time	yes
Weighing function	yes
Weighing range [g]	5 - 4000
Weighing resolution [g]	1
Load capacity weighing function max. [kg]	4
Weighing accuracy	±(0.3%+2) g
Vessels detection	yes
Ramp programming	yes
Dimensions (W x H x D) [mm]	300 x 350 x 250
Weight [kg]	8.5
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 31
USB interface	yes
Bluetooth interface	yes
Voltage [V]	220 - 240
Frequency [Hz]	50/60
Power input [W]	1000