



designed for scientists



S 25 KD - 18 G Dispersing tool

/// Data Sheet

Dispersing tool for the dispersers T 25 digital, T 25 easy clean digital/control

Type of sealing and bearing: Ball-bearing with PTFE sealing and FFKM O-ring

Product-touching material: AISI 316L, PTFE, FFKM

Suitable for solvents: Yes

Sterilizable: all methods (except ball-bearing)

Suitable for vacuum: Yes

Max. working temperature [°C]: 150



designed for scientists

Shaft length [mm]: 194

Diameter stator/rotor [mm]: 18/12.7

Gap between [mm]: 0.3

Recommend emersion depth [mm]: 40 - 185

Recommend working range [ml]: 10 - 1,500



designed for scientists

Technical Data

Volume range (H ₂ O) [l]	0.01 - 1.5
Stator diameter [mm]	18
Rotor diameter [mm]	12.7
Gap between rotor and stator [mm]	0.3
allowable Speed max. [rpm]	25000
Circumferential speed max. [m/s]	16.6
Immersion depth [mm]	40 - 185
Shaft length [mm]	194
Material in contact with medium	AISI 316L / PTFE / FFPM
pH range	2 - 13
Working temperature max. [°C]	150
Sterilization methods	wet chemical
Vacuum [mbar]	100
Ultimate fineness, suspensions [µm]	10 - 50
Ultimate fineness, emulsions [µm]	1 - 10
Weight [kg]	0.336
Permissible ambient temperature [°C]	5 - 40