



SY 1000 Reactor vessel

/// Data Sheet

Double-walled reactor vessel including accessories for the EasySyn reactor system. Volume: 1000 ml Flange size: DN 100 Including stainless steel metal adapter M 16x1 (Male) to connect temperature hoses.

Scope of delivery: Glasreactor incl. metal adapter

2



Technical Data

Volume [l]	1
Fill level diameter ratio	1.25
Fill level at nominal volume [mm]	96
Vessel inner diameter [mm]	120
Vessel outer diameter [mm]	160
Height (room dimension) [mm]	251
Width (room dimension) [mm]	218
Depth (room dimension) [mm]	165
Flange type	acc. DIN 12214 with circular groove
Flange dimension	DN100
Flange collar diameter [mm]	108
Bottom shape	Torispherical head
Tempering jacket filling capacity [L]	0.71
Tempering jacket inlet connection	DN 15 (tech-flange)
Tempering jacket inlet inner diameter [mm]	15
Vacuum application	yes
Tempering jacket outlet connection	DN 15 (tech-flange)
Tempering jacket oulet inner diameter [mm]	15
Thread closure system	M16x1
Width across flats	WAF 22
Material closure system	stainless steel 1.4404
Reactor vessel material	borosilicate glass 3.3 DIN ISO 3585
Working temperature [°C]	-50 - 230
Useable volume [ml]	120 - 1150
Useable volume with temperature probe min. [ml]	260
Pressure max.	atmospheric pressure
Attainable vacuum [mbar]	3
Material in contact with medium	borosilicate glass 3.3 DIN ISO 3585