



designed for scientists



SP-2

/// Data Sheet

Standard spindle



designed for scientists

Technical Data

Spindle geometry	Disc
Connection	Thread M2.5 LH
Quick plug connector	yes
Hook connector	yes
Diameter [mm]	18.7
Immersion depth [mm]	50
Spindle length [mm]	115
Mounting Bracket	yes
Sample container:	600mL beaker low
Viscosity Accuracy (FSR) [%]	1
Viscosity Repeatability (FSR) [%]	0.2
Min. FSR match ROTAVISC lo-vi [mPa.s]	150.0
Max. FSR match ROTAVISC lo-vi [mPa.s]	29994
Min. FSR match ROTAVISC me-vi [mPa.s]	1600.0
Max. FSR match ROTAVISC me-vi [mPa.s]	320000
Min. FSR match ROTAVISC hi-vi I [mPa.s]	3200.0
Max. FSR match ROTAVISC hi-vi I [mPa.s]	640000
Min. FSR match ROTAVISC hi-vi II [mPa.s]	12800
Max. FSR match ROTAVISC hi-vi II [mPa.s]	2560000
Material in contact with medium	stainless steel 1.4404
Dimensions (W x H x D) [mm]	20 x 117 x 20
Weight [kg]	0.024
Permissible ambient temperature [°C]	5 - 40