



designed for scientists



VOL-SP-10.4

/// Data Sheet

VOL-SP-10.4 is an optional spindle for an extended viscosity range. It is especially suitable for sample volumes of 10.4 ml.



designed for scientists

Technical Data

Spindle geometry	Cylinder
Connection	Thread M2.5 LH
Hook connector	yes
Diameter [mm]	11.8
Immersion depth [mm]	45.3
Spindle length [mm]	76.7
Sample volume [ml]	10.4
Flow Jacket	yes
Mounting Bracket	yes
Sample container:	Specified chamber
Working temperature max. [°C]	100
Viscosity Accuracy (FSR) [%]	2
Viscosity Repeatability (FSR) [%]	0.2
Min. FSR match ROTAVISC lo-vi [mPa.s]	117.2
Max. FSR match ROTAVISC lo-vi [mPa.s]	23433
Min. FSR match ROTAVISC me-vi [mPa.s]	1250
Max. FSR match ROTAVISC me-vi [mPa.s]	250000
Min. FSR match ROTAVISC hi-vi I [mPa.s]	2500
Max. FSR match ROTAVISC hi-vi I [mPa.s]	500000
Min. FSR match ROTAVISC hi-vi II [mPa.s]	10000
Max. FSR match ROTAVISC hi-vi II [mPa.s]	2000000
Material in contact with medium	stainless steel 1.4404
Dimensions (W x H x D) [mm]	14 x 79 x 14
Weight [kg]	0.035
Permissible ambient temperature [°C]	5 - 40