

## CORIO C-BT9

The open heating bath circulators of the new CORIO series feature high-quality transparent bath tanks.

### Product features

- Models for internal applications
- Bright, white, easy to read display
- Very quiet
- Precise temperature control



### Performance values

115V/60Hz (Nema N5-15 Plug)	
Heating capacity kW	1
Viscosity max. cST	1
Circulation capacity flow rate l/min	6
Circulation capacity pressure psi	1.5
Power A	10

### Technical data

Available voltage versions		Bath	
Order No.	9 011 309	Bath tank	Polycarbonat
Available voltage versions:		Usable bath opening in. (W x L / D)	9.1 x 5.9 / 5.9
9011309.22	100-115V/50-60Hz (Nema N5-15 Plug)		
9011309.33.chn	230V/50-60Hz (CN Plug)		
9011309.33	230V/50-60Hz (Schuko Plug - CEE 7/4 Plug Type F)		
9011309.04	230V/50-60Hz (UK Plug Type BS1363A)		
9011309.05	230V/50-60Hz (CH Plug Type SEV 1011)		
Other		Electronics	
Classification	Classification I (NFL)	Temperature control	PID1
IP Code	IP 21	Absolute temperature calibration	1 Point Calibration
Pump type	Immersion Pump	Temperature display	LED
		Temperature setting	Keypad

Dimensions and volumes		Temperature values	
Weight lbs	8.6	Setting the resolution of the temperature display °C	0.1
Dimensions in. (W × L × H)	12.6 x 15 x 15	Working temperature range °C	+20 ... +100
Filling volume l	6 ... 9	Temperature stability °C	±0.03
		Ambient temperature °C	+5 ... +40
		Temperature display resolution °C	0.01 ... 0.1

For applications near or below ambient temperature: use a cooling coil or JULABO immersion cooler.

### All Benefits



**100% Checked.**  
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



**JULABO. Quality.**  
Highest standards of quality for a long product life.



**Green technology.**  
Development consistently applied environmentally friendly materials and technologies.



**Quick start.**  
Individual JULABO consultation and comprehensive manuals at your disposal.



**Satisfied customers.**  
11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



**Services 24/7.**  
Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at [www.julabo.us](http://www.julabo.us).



**Brilliant.**  
Very bright display makes it easy to read even from a distance.



**Connection. Easy.**  
Inclined pump connections (M16×1) facilitate the connection of applications. Each unit includes 2 barbed fittings of 8/12 mm diameter each.



**Everything at the front.**  
All operating controls and safety functions are accessed easily and comfortably from the front.



**Exact.**  
You can rely on it. PID1 control and 'Active Cooling Control' make the new CORIO precise and perfect.



**Locked in.**  
The lockable power plug guarantees safe connection. More process safety.



**Switch on. And off you go.**  
Intelligent operating concept. Ready for operation with just a few quick and easy steps.



**Timer. Integrated.**  
CORIO circulators include an integrated timer function. When the set time has elapsed, a signal sounds and the device switches off. Setting range: 0 ... 999 minutes.



**Early warning system for low liquid level**  
Maximum safety for applications, optical and audible alarm, allows user to refill bath fluid before the unit shuts down