

PRESTO W55 Process system

The powerful W55 regulates temperatures with high precision and convinces with faster cool-down and heat-up times. It is ideal for use in large external applications such as reactor temperature control, material stress testing or temperature simulation.



Product features

- For highly precise, external temperature applications
- Rapid heating and cooling
- Wide working temperature ranges without changing fluids
- Highest performance with small footprint
- Space-saving design optimizes space utilization in your lab
- Pump pressure up to 3.2 bar, max. flow rate 76 l/min
- Temperature stability $\pm 0.05\text{ }^{\circ}\text{C}$... $\pm 0.1\text{ }^{\circ}\text{C}$
- 5,7" industrial color TFT touch screen
- Connections for USB, Ethernet, RS232, and Alarm output
- Modbus
- SD-Card slot
- Analog connections, RS485, Profibus DP (accessory)
- Second external Pt100 sensor connection (accessory)

Performance values

230V/3PPE/60Hz (Without Plug)	
Heating capacity kW	15
Viscosity max. cST	50
Pump capacity flow rate l/min	35 ... 80
Pump capacity flow pressure psi	7 ... 46.4
Power A	60

Order No.	9421552.16						
Cooling capacity 1 (Ethanol)							
$^{\circ}\text{C}$	20	0	-10	-20	-30	-40	-50
kW	15	10	6.5	4	2.5	1.2	0.3
* Performance specifications measured in accordance with DIN 12876. Cooling capacities up to 20 $^{\circ}\text{C}$ measured with ethanol; over 20 $^{\circ}\text{C}$ with thermal oil unless otherwise specified. Performance specifications apply at an ambient temperature of 20 $^{\circ}\text{C}$. Performance values may differ with other bath fluids.							
Refrigerant stage 1							
Refrigerant	R452A						
Filling volume g	1600						
Global Warming Potential for R452A	2140						
Carbon dioxide equivalent t	3.424						

208V/3PPE/60Hz (Without Plug)	
Heating capacity kW	12.5
Viscosity max. cST	50
Pump capacity flow rate l/min	35 ... 80
Pump capacity flow pressure psi	7 ... 43.5
Power A	55

Order No. 9421552.16

Cooling capacity 1 (Ethanol)

°C	20	0	-10	-20	-30	-40	-50
kW	15	10	6.5	4	2.5	1.2	0.3

* Performance specifications measured in accordance with DIN 12876. Cooling capacities up to 20 °C measured with ethanol; over 20 °C with thermal oil unless otherwise specified. Performance specifications apply at an ambient temperature of 20 °C. Performance values may differ with other bath fluids.

Refrigerant stage 1

Refrigerant	R452A
Filling volume g	1600
Global Warming Potential for R452A	2140
Carbon dioxide equivalent t	3.424

Technical data

Available voltage versions	
Order No.	9 421 552
Available voltage versions:	
9421552.16	208-230V/3PPE/60Hz (Without Plug) (R452A)
9421552.07	400V/3PNPE/50Hz (Plug 32A CEE) (R452A)
9421552.S1.07	400V/3PNPE/50Hz (Plug 32A CEE) (R449A)


Cooling	
Cooling of compressor	1-stage Water
Cooling water temperature max. °C	35
Cooling water pressure max. psi	87
Cooling water difference pressure psi	7.3
1.0Cooling water consumption l/min	2 ... 12


Other	
Sound pressure level dbA	65
Classification	Classification III (FL)
IP Code	IP 20
Pump type	Centrifugal Pump

Electronics	
Interfaces	Alarm output, Ethernet, Modbus, RS232, USB, SD memory card standard Profibus, RS485, Reg/Eprog, Standby-Input optional
External pt100 sensor connection	integrated
2nd external Pt100 sensor connection	accessory
Integrated programmer	8x60 steps
Temperature control	ICC
Absolute temperature calibration	3 Point Calibration
Temperature display	5.7" TFT Touchscreen


Dimensions and volumes		Temperature setting	Touchscreen
Internal usable expansion volume l	7.5	Temperature values	
Minimal process volume l	11.5	Setting the resolution of the temperature display °C	0.01
Active heat exchanger volume l	7	Working temperature range °C	-55 ... +250
Weight lbs	634.9	Temperature stability °C	±0.05 ... ±0.1
Cooling Water Connection in	G¾	Ambient temperature °C	+5 ... +40
Dimensions in. (W × L × H)	24 x 33.3 x 49.2	Temperature display resolution °C	0.01
Pump connections	M30x1.5 male		


All Benefits

- 


Touch display. Perfect operation.
With the touch display, the user always has an overview of all values and functions. The intuitive and multilingual menu structure enables perfect control.
- 


Convenience for several users
Administrator level for customizing instrument settings, user levels with limited permissions for fast and safe defined access, password protection, all levels adjustable
- 

100 % Cooling capacity
'Active Cooling Control' for cooling available throughout the entire working temperature range, fast cool-down even at higher temperatures
- 


Intelligent temperature control.
Intelligent cascade control - automatic and self-optimizing adaptation of the PID control parameters with external stability of +/- 0.05 °C.
- 


Full control
'Temperature Control Features', for individual optimization, access to all important control parameters, additional settings for band limit, limits, co-speedfactor etc.
- 


Control of the external application
External Pt100 sensor connection for precise measurement and control directly in the external application
- 


Highest measuring accuracy
'Absolute Temperature Calibration' for manual compensation of a temperature difference, 3-point calibration
- 


Intelligent pump system
Reliable and consistent pump capacity, electronically adjustable pump stages or pressure value, automatic adjustment of pump capacity to viscosity
- 

Many interfaces.
Straight-forward remote control, data management, and integration into process structures. USB, Ethernet, RS232, SD card, and alarm off are permanently integrated. Further interfaces available as accessories.
- 

Space-saving footprint
All connections as well supply and exhaust air are located at the front or rear, no venting grids on the sides, units can be placed close to each other or the application
- 

Continuous operation up to +40 °C
Robust temperature control instrument, continuous operation even at ambient temperatures of up to +40 °C
- 

Maximum safety.
Classification III according to DIN12876-1 enables safe operation, even with flammable fluids. Automatic switch-off in the event of high temperature or low liquid level.
- 

Duplicate safety
Adjustable high temperature cut-off for internal tank and for integrated expansion vessel
- 

For flammable bath fluid
Classification III (FL) according to DIN 12876-1



Quick support
If an error occurs, the integrated Black-Box function permits fast diagnosis by the JULABO service team



100% Checked.
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Green technology.
Development consistently applied environmentally friendly materials and technologies.



JULABO. Quality.
Highest standards of quality for a long product life.



Quick start.
Individual JULABO consultation and comprehensive manuals at your disposal.



Satisfied customers.
11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



Services 24/7.
Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.