

Product Name:	PH-ABT-HC-RFC7SA-CAD
Description:	<p>Premier Pharmacy/Vaccine Refrigerator & Freezer Combination with Controlled Auto Defrost Freezer</p> <p>5.2 cu. ft. capacity (Refrigerator) / 1.0 cu. ft. capacity (Freezer)</p> <p>Two exterior swing doors (solid door refrigerator/solid door freezer), right hinged, not reversible</p> <p>Microprocessor temperature controller, refrigerator and freezer</p> <p>Digital temperature display with sample simulated probe, refrigerator and freezer</p> <p>Adjustable operating temperature range:</p> <p>Refrigerator: 36°F - 46°F (2°C - 8°C)</p> <p>Freezer: 5°F – -13°F (-15°C – -25°C)</p> <p>Defrost:</p> <p>Auto defrost cycle every 6 hours: (at Set Point -11°F /-24°C)</p> <p>Max air temp in empty freezer: 5°F (-15°C)</p> <p>Max air temp in loaded freezer: 3°F (-16°C)</p> <p>Max sample temp in empty freezer: 0°F (-18°C)</p> <p>Max sample temp in loaded freezer: -4°F (-20°C)</p> <p>Refrigerator/Freezer freestanding thermometer with 3 year certificate of calibration, with min/max memory, °F/°C switchable</p> <p>Audible and visual high and low temperature alarms, refrigerator and freezer</p> <p>Remote alarm contacts, refrigerator and freezer</p> <p>5 adjustable shelves total with guard rail on back to prevent product from being pushed against back wall</p> <p>3 adjustable shelves, Refrigerator; 2 adjustable shelves, Freezer</p> <p>Bottom footed shelf to allow air circulation, Refrigerator and Freezer</p> <p>Vaccine storage power cord warning label</p> <p>Forced draft circulation Refrigerator</p> <p>Keyed door locks</p> <p>Magnetic door gasket for positive seal</p> <p>Integrated door handles</p> <p>Leveling legs</p> <p>Stacking kit</p> <p>Two probe access ports (3/8"); one, refrigerator/one, freezer</p> <p>White powder coated exterior</p> <p>HFC-free refrigerant (R600a), foam insulation and packaging</p> <p>Pharmacy refrigerator/freezer toolkit and temperature logs</p> <p>Two year parts and labor warranty, plus an additional three year compressor parts warranty</p> <p>Pyxis®, Omnicell® and AcuDose RX® compatible</p> <p>Exterior dimensions: 23 ¾"W x 24" D x 53 1/8"H</p> <p>Controlled Auto Defrost freezer, Patented Technology</p> <p>Cycle defrost refrigerator</p>

	<p>115V, 60 Hz, 1.3 Amps refrigerator, 1 Amp freezer, 1/6 HP refrigerator, 1/8 HP freezer UL/C-UL listed Shipping weight: 215 lbs. *Please note this unit requires 2 outlets.</p>
--	---