24" Ductless Fume Hood

Model # SS-224-DCH

The **24" Wide Ductless Fume Hood** helps protect the operator and environment from hazardous fumes or particulate generated from applications performed within the hood. Its small structure makes it a great fume extraction solution and addition to a lab or room that has limited space or requires only a small containment area. This lightweight hood provides optimal fume control for field-testing applications because of its ability to be easily transported and its reliable operation. Also as an option, this system can include a removable spill tray for chemical spills.

The **24" Ductless Fume Hood's** powerful fan directs fumes into the filter chamber containing high quality filter media selected depending on the application. Filter media choices include **HEPA** [up to 99.97% efficiency on particles 0.3 microns and larger], **ASHRAE** [up to 95% efficiency on particles 0.5 microns and larger, **Activated Carbon**, and **specialty-blended filtration** [i.e. acid gas, mercury, aldehyde, and ammonia].

Typical uses for the **24" Ductless Fume Hood** include chemical fumes, pharmaceutical compounding, soldering applications, dust removal, biological applications, and a variety of applications requiring fume and dust removal. The **24" Ductless Fume Hood** can provide an effective and economical solution for many commercial, medical, laboratory and industrial applications that require a small containment area. For additional visibility, a transparent version is available at extra cost.

Our line of ductless fume hoods is not intended for sterile compounding applications.





24" Ductless Fume Hood



24" DCH provides fume control for a variety of laboratory applications.

Product Features

- Includes: clear anti-static vinyl curtains, velometer, and LED light
- Optional: variable speed controller (115V only), hour counter, and spill tray
- **Standard Sizes:** 12", 18", 24", 30", 40", 50", 60", and 70" (custom sizes available)
- · Quiet operation
- Long filter life
- · Simple, quick "no tool" filter change
- Portable and lightweight
- Reliable, low maintenance operation



21221 FM 529 Rd, Cypress, TX 77433 1.800.799.4609 • sales@sentryair.com

Product Specifications





Shown with outer dimensions. Dimensions are approximate.

Hood Dimensions	Outer: 24" x 26" x 25"
(D x W x H)	Interior: 23.5" x 24" x 24"
(2 //,	Access Area: 8" x 24"
Hood Material	Sides: 0.25" white acrylic
	Base: 0.5" white high
	density polyethylene
	Top: 0.5" clear
	polycarbonate
	Front Window: 0.25"
Diameter State of the Control	clear polycarbonate
Blower Dimensions	10.5"L x 8" W x 8.5" H
Diamer Make 1	16 Ga. carbon steel with
Blower Material	polyester epoxy coating
	on all surfaces
Weight	55 lbs
(approximately)	
Air Volume	80 CFM
(approximately)	(varies with filter media)
	Carbon Pre-filter + HEPA
Inlet Velocities on	Filter - 100 FPM
High (approximately)	Carbon Pre-filter + Heavy
Tilgii (approximatery)	Duty Carbon Filter –
	60 FPM
Electrical	115/1/60, 0.3 amps
	220/1/50, 0.2 amps
	8' grounded power cord
	with NEMA 5-15P plug
Sound Level	55 dba
Maximum	Operating temperature
Temperature	not to exceed 170° F
Main Filter Options	HEPA (up to 99.97%
	efficient on particles
	down to 0.3 microns)
	ASHRAE (up to 95%
	efficient on particles
	down to 0.5 microns)
	Activated Carbon
	Specialty-blended Filter
	Media (i.e. acid gas,
	mercury, aldehyde, and ammonia)
	·
Warranty	Limited two-year warranty
	from date of shipment on defects due to materials
	or workmanship.
	5,843,197
Patent #	1 5 2/13 10/



21221 FM 529 Rd Cypress, TX 77433 1.800.799.4609 sales@sentryair.com

www.sentryair.com