## **60" Ductless Fume Hood**

## Model # SS-360-DCH

The 60" Wide Ductless Fume Hood combines powerful air flow with a sturdy and compact enclosure for optimal respiratory and environmental protection. This fume hood helps protect the operator and environment from hazardous fumes or particulate generated from applications performed within the hood.

The **60" Ductless Fume Hood's** powerful fan directs fumes into the filter chamber containing high quality filter media selected depending on the application. Filter media choices include **HEPA** [up to 99.97% efficiency on particles 0.3 microns and larger], **ASHRAE** [up to 95% efficiency on particles 0.5 microns and larger, Activated Carbon, and specialty-blended filtration [i.e. acid gas, mercury, aldehyde, and ammonial.

Typical uses for the **60" Ductless Fume Hood** include chemical fumes, pharmaceutical compounding, soldering applications, dust removal, biological applications, and a variety of applications requiring fume and dust removal. The **60" Ductless Fume Hood** can provide an effective and economical solution for many commercial, medical, laboratory, and industrial applications. For additional visibility, a transparent version is available at extra cost.

Our line of ductless fume hoods is not intended for sterile compounding applications.





60" Ductless Fume Hood



60" DCH provides chemical fume control for use with various substances.

## **Product Features**


- Includes: variable speed controller (115V only), velometer, and LED light
- **Optional:** clear anti-static vinyl curtains, Magnehelic Gauge, and hour counter
- Standard Sizes: 12", 18", 24", 30", 40", 50", 60", and 70" (custom sizes available)
- · Quiet operation
- · Long filter life
- · Simple, quick "no tool" filter change
- · Portable and lightweight
- Reliable, low maintenance operation



21221 FM 529 Rd, Cypress, TX 77433 1.800.799.4609 • sales@sentryair.com

## **Product Specifications**





Shown with outer dimensions. Dimensions are approximate.

Outer: 24" x 62" x 25" **Hood Dimensions** Interior: 23.5" x 60" x 24"  $(D \times W \times H)$ Access Area: 8" x 60" Sides: 0.25" white acrylic Base: 0.5" white high density polyethylene **Hood Material** Top: 0.5" clear polycarbonate Front Window: 0.25" clear polycarbonate **Blower Dimensions** 15.5"L x 13" W x 14.5" H 16 Ga. carbon steel with **Blower Material** polyester epoxy coating on all surfaces 140 lbs Weight 350 CFM **Air Volume** (approximately) (varies with filter media) Carbon Pre-filter + HEPA Filter - 100 FPM high, 25 FPM low **Inlet Velocities on High (approximately) Carbon Pre-filter + Heavy Duty Carbon Filter -**70 FPM high, 20 FPM low 115/1/60, 2 amps 220/1/50, 0.75 amps **Electrical** 8' grounded power cord with NEMA 5-15P plug **Sound Level** 61 to 66 dba (low to high) **Maximum** Operating temperature **Temperature** not to exceed 170° F **HEPA** (up to 99.97% efficient on particles down to 0.3 microns) **ASHRAE** (up to 95% efficient on particles **Main Filter** down to 0.5 microns) **Options Activated Carbon Specialty-Blended Filter** Media (i.e. acid gas, mercury, aldehyde, and ammonia) Limited two-year warranty from date of shipment on Warranty defects due to materials or workmanship. 5,843,197 Patent #



21221 FM 529 Rd Cypress, TX 77433 1.800.799.4609 sales@sentryair.com

www.sentryair.com