

ENGINEERS AND MANUFACTURERS OF ULTRA-LOW FREEZERS

## *SO-LOW CHEST STYLE FREEZER TO -40°C*

### *MODEL C40-2*

**2 Cubic Ft. (56 liters) Chest – Temperature Range: 0°C to -40°C**

## **Mini Chest Freezer**

### ***Specifications:***

* Capacity	2 cubic ft. / 56 liters
* Temperature Range	0°C to -40°C
* Dimensions	
* Exterior W x D x H	25.25" x 25.75" x 40" 64 x 65 x 101 (cm)
* Interior W x D x H	17" x 14" x 14" 43 x 35 x 35 (cm)

### **TEMPERATURE CONTROL**

Microprocessor control displays set point and chamber temperature.

### **ALARM SYSTEM WITH RELAY**

The battery operated alarm system will emit an audible and visual signal when there is a mechanical or electrical failure. The alarm has an over and under temperature setting, alarm silencing switch, and battery test switch. Also provided is a relay for remote alarm hook-up.

### **REFRIGERATION SYSTEM**

A So-Low single stage system with one hermetic compressor. CFC & HCFC free refrigerants.

### **CONSTRUCTION**

Chamber is 14-ga. Zinc coated galvanized steel. Exterior is 16-ga. steel. Power coated cool gray.

### **VOLTAGE**

115 volts 60 hertz, 1 phase.  
15 AMP dedicated circuit required.  
ETL electrical approval.

### **TECHNICAL SUPPORT**

Supplied by Nation-Wide-Network of service companies.



Specifications subject to change without notice