

ENGINEERS AND MANUFACTURERS OF ULTRA-LOW FREEZERS

SO-LOW CHEST STYLE FREEZER TO -85°C MODEL C85-12

**12 Cubic Ft. (340 liters) Chest – Temperature Range: -40°C to -85°C
Top Opening**

Specifications:

* Capacity	12 cubic ft. / 340 liters
* Temperature Range	-40°C to -85°C
* Dimensions	
* Exterior W x D x H	65.5" x 32" x 47.5" 166 x 81 x 120 (cm)
* Interior W x D x H	55" x 19" x 20" 139 x 48 x 50 (cm)

TEMPERATURE CONTROL

Microprocessor control displays set point and chamber temperature.

ALARM SYSTEM WITH RELAY

The battery operated alarm system will emit an audible and visual signal when there is a mechanical or electrical failure. The alarm has an over and under temperature setting, alarm silencing switch, and battery test switch. Also provided is a relay for remote alarm hook-up.

REFRIGERATION SYSTEM

A So-Low cascade system with two hermetic compressors. CFC & HCFC free refrigerants

CONSTRUCTION

Chamber is 14-ga. Zinc coated galvanized steel. Exterior is 16-ga. steel. Power coated cool gray.

VOLTAGE

115 volts 60 hertz, 1 phase.
20 AMP dedicated circuit required.
ETL electrical approval.

TECHNICAL SUPPORT

Supplied by Nation-Wide-Network of service companies.

Specifications subject to change without notice

