

ENGINEERS AND MANUFACTURERS OF ULTRA-LOW FREEZERS

## *SO-LOW LABORATORY & PHARMACY PASS-THRU REFRIGERATOR MODEL DH4-25PT*

*“SETTING TEMPERATURE STANDARDS IN EVERY LAB”*

**25 Cubic Ft. Upright – Temperature Range: 2°C to 8°C**

**Glass doors on front and back**

### *Specifications:*

|                      |   |
|----------------------|---|
| * Capacity           | 25 cubic ft.                              |
| * Temperature Range  | 2°C to 8°C                                |
| * Dimensions         |   |
| * Exterior w x d x h | 26" x 37.5" x 81.5"<br>66 x 95 x 207 (cm) |
| * Interior w x d x h | 23" x 30" x 59"<br>58 x 76 x 149 (cm)     |

### *Features:*

|                     |  |
|---------------------|--|
| Temperature Control | Digital display with<br>Hi/Low alarm<br>Alarm Relay Dry Contacts           |
| Construction        | Stainless Interior and Exterior  |
| Door                | Glass doors front and back, lockable                                       |
| Casters             | Four, locking  |
| Shelves             | 3 epoxy coated   |
| Interior Light      | Fluorescent  |
| Insulation:         | Polyurethane foam  |
| Refrigerant:        | R-134A   |
| Compressor          | 1/3 hp   |
| Air Circulation     | Forced air   |
| Evaporator          | Fin and tube   |
| Defrost             | Cycle, Auto  |
| Voltage:            | 115/60/1   |
| Running Amps        | 6.0  |
| Supply Plug         | 5-15P NEMA   |
| Shipping Weight     | 500 lbs.   |
| Warranty-(Domestic) | Three year parts and labor<br>Compressors additional<br>2 years, no labor. |



Specifications subject to change without notice.