

ENGINEERS AND MANUFACTURERS OF ULTRA-LOW FREEZERS

SO-LOW CHEST STYLE FREEZER TO -40°C MODEL NC40-27

27 Cubic Ft. (766 liters) Chest – Temperature Range: 0°C to -40°C Top Opening

Specifications:

* Capacity
* Temperature Range
* Dimensions
* Exterior W x D x H
* Interior W x D x H
* For the second second

<u>COLOR TOUCH SCREEN</u> <u>TEMPERATURE CONTROL</u>

Touch Screen control Displays set point and chamber temperature Hi/Low Alarm W/ Email and SMS notification Alarm Relay Dry Contacts Power Failure Dry Contacts Battery Back-up Viewable Temperature graph Data logging downloadable via USB or FTP Multi-Level Security VNC Remote Access

ALARM SYSTEM WITH RELAY

The battery operated alarm system will emit an audible and visual signal when there is a mechanical or electrical failure. The alarm has an over and under temperature setting, alarm silencing switch, and battery test switch. Also provided is a relay for remote alarm hook-up.

REFRIGERATION SYSTEM

A So-Low single stage system with one hermetic compressors. CFC & HCFC free refrigerants

VOLTAGE

20 AMP dedicated circuit required. ETL electrical approval.

Specifications subject to change without notice

