

## *SO-LOW UPRIGHT FREEZER TO -80°C*

### *MODEL U80-28*

**28 Cubic Ft. (792 liters) Upright – Temperature Range: -40°C to -80°C**

#### **Upright Freezer**

##### ***Specifications:***

* Capacity	28 cubic ft. / 792 liters
* Temperature Range	-40°C to -80°C
* Dimensions	
* Exterior W x D x H	54" x 37" x 79 ½" 137 x 93 x 201 (cm)
* Interior W x D x H	38" x 25" x 51" 96 x 63 x 130 (cm)

##### **TEMPERATURE CONTROL**

Microprocessor control displays set point and chamber temperature.

##### **ALARM SYSTEM WITH RELAY**

The battery operated alarm system will emit an audible and visual signal when there is a mechanical or electrical failure. The alarm has an over and under temperature setting, alarm silencing switch, and battery test switch. Also provided is a relay for remote alarm hook-up.

##### **REFRIGERATION SYSTEM**

A So-Low cascade system with two hermetic compressors. CFC & HCFC free refrigerants

##### **CONSTRUCTION**

Chamber is 14-ga. Zinc coated galvanized steel. Exterior is 16-ga. steel. Power coated cool gray.

##### **VOLTAGE**

115/60/1 - 208/60/1 - 230/60/1 - 220/50/1  
20 AMP dedicated circuit required.  
ETL electrical approval.

##### **TECHNICAL SUPPORT**

Supplied by Nation-Wide-Network of service companies.

Specifications subject to change without notice

